

Catering

coldline



At Coldline we create
technology which simplifies
the daily work of chefs
and professional restaurant cooks.



Cold culture and technology

The human factor

At Coldline we value a dialogue with the men and women who work in the kitchen. It helps us to develop ideas and technologies which allow us to improve our products.

“Cold” culture

In our laboratory, we monitor our appliances in extreme conditions. This ensures that they will be able to perform optimally even when used intensively. We subject them to strict field testing at our modern cooking center, where our group of corporate chefs validate all our new products.

100% integrated process

Research and development, design and production activities are carried out exclusively in our factories in Torreglia (PD), Italy. All business processes are founded upon the principles of reliability, efficiency and energy savings.



The right level of cold for every cook

We offer ideal solutions for every type of catering company. It is the wide range of sizes, energy saving and high performance qualities which define Coldline appliances.



Catering

Restaurants
Bed & breakfasts
Fast foods
Snacks
Butchers
Fishmongers
Hotels



Cooking centres

Companies
Schools
Hospitals
Ships
Catering



Retail outlets

Supermarkets
Shopping centres
Franchising chains
Service areas

Blast
chillers



modi

Blast chilling

Blast freezing

Manual cycle

Thawing

coldline

MODI, the multifunctional blast chiller

The days of blast chillers being limited to chilling food are over. The modern catering company requires a greater range of tools. So we developed the MODI.

A single device which allow you to carry out numerous functions, and which operates 24 hours a day, not only saving you space, but also money; it is no longer necessary to purchase additional appliances that you do not need.





Up & Active,
the ideal choice
for your business


UP -40° +10°C	ACTIVE -40° +65°C	
■	■	Blast chilling Rapid cooling of uncooked and cooked food to +3°C. Evenly chilled throughout
■	■	Blast freezing Rapid cooling of uncooked and cooked food to -18°C. Evenly chilled throughout
■	■	Manual cycle Maintain foodstuffs at a temperature between -40°C to +10°C (Up) and -40°C to +65°C (Active)
-	■	Thawing Quickly thaws food safely, and maintain the original quality
-	■	Holding Maintain dishes at a temperature ready to serve
-	■	Desiccation It gently dehydrates foodstuffs and lengthens its storage times
-	■	Proving and retarder proving Create the perfect microclimate for perfect proving
-	■	Chocolate crystallisation Pralines, chocolates and chocolate bars crystallize in a few minutes



Hot or cold? Think: MODI


MODI dynamically manages the intensity of the cold and the heat by constantly modulating temperature, ventilation and the cycle time. A technology that preserves the characteristics of foodstuffs, and extends their shelf life.

Protected by robust tempered glass, the MODI touch screen 4.3" makes it simple to use. With one touch you can access available programs, or create one of your own in the personal menu.




Customised recipe book

You have the possibility to customise programs for each type of food.



Personal layout

You can change the position of the recipe keys by creating your own layout.



Manual cycle

You can work at the temperature you prefer, by choosing the optimum ventilation intensity.

Blast chilling

It rapidly cools food to a uniform +3°C, blocks bacterial proliferation, and increases storage time by up to 70%, while maintaining the quality.

Blast chilling green beans with MODI

Stops the cooking process, preserves the taste, consistency and colour

Green beans chilled at room temperature

The product oxidizes, loses consistency and some of the nutrients



Preserve for longer

The temperature range of +65°C and +10°C is the ideal condition for bacteria to proliferate, which shortens the shelf life of the foods. The intense cold of MODI extends the period of preservation, maintaining its colour, flavour and consistency.

Planning and flexibility

Increasing the storage period of food means that you will not have to repeat the same preparations every day. You can make larger quantities of the product for future use, refrigerate and serve the required portions as required.

Blast freezing

Rapidly blast freezing to -18°C causes the formation of micro-crystals in the liquid, which means fibers, structure and taste remain intact.

Freezing salmon

Slow freezing causes the formation of macro-crystals, which tears fibers and leads to the loss of liquids which contain nutrients

Blast freezing salmon with MODI

Rapidly blast freezing causes the formation of micro-crystals, which preserves the fibres and structure of the salmon



Healthy as a fish

Thanks to the power and the delicacy of the cold generated by MODI you can protect the texture and eliminate any risk of Anisakis. After thawing, you will find a fresh and easy-to-eat meat.

Organisation and convenience

You can effectively combine blast freezing with the purchase of ingredients from trusted suppliers. Avoiding the purchase of frozen and semi-finished industrial products is the first step in improving your income.



Manual cycle

MODI is a unique technology. It allows you to adjust the temperature from -40°C to $+10^{\circ}\text{C}$ (Up) and from -40°C to $+65^{\circ}\text{C}$ (Active) with an adjustable ventilation intensity from 25% to 100%. What other appliance offers you such a wide range of flexibility?



Thawing

Thawing is one of the slowest and most delicate processes in the kitchen. MODI quickly thaw out food safely, maintains the original quality and prevents the proliferation of bacteria.



Holding

Keep your dishes at serving temperature. Thanks to MODI, all your dishes, from the first to the last, will leave the kitchen at the ideal temperature, no matter how long the process takes. The unsold portions can be blast chilled or blast frozen.

Desiccation

Dehydrate fruit, vegetables, mushrooms and legumes, and have them available throughout the season. You can also make special flours and flavorings for your dishes.



Proving and retarder proving

For perfect proving it is necessary that the dough remains at the correct temperature for exactly the right amount of time, without sudden changes in humidity. MODI creates the best micro-climatic conditions for obtaining the best results.



Chocolate crystallisation

Crystallise pralines, chocolates and chocolate bars in just a few minutes; their appearance and crunchy texture, a testimony to the quality of your work.





MODI, a hub in the Cosmo

What is Cosmo?

Cosmo is an innovative wi-fi technology which allows you to connect all the Coldline refrigerators in your workshop to the MODI blast chiller and monitor them from your smartphone. Therefore, you are always able to check on their status.

No stress

Refrigerators work non-stop, 24 hours a day. The quality of the food you have selected depends on them functioning perfectly. Cosmo detects any faults caused by power cuts or improper use and sends an immediate notification to your smartphone.

Efficiency is monitored

Cosmo constantly compares the performance of your Coldline appliance with the ideal parameters. In cases of significant differences, it suggests the necessary maintenance to ensure the best performance.

Software is always updated

Thanks to Cosmo the software of your Coldline device can receive periodic updates, equipping it with the most recent developments.

MODI technology



Principal characteristics

			
Modular base Allows installation on wheels, feet, fixed or mobile base.	Electronic thermostatic valve Regulates the quantity of the refrigerant fluid injected, improving performance by 25% and reducing consumption.	Replaceable gaskets with high performance insulation Triple chamber geometry with innovative D7 compound, which produces 35% higher insulation efficiency than traditional models.	Air flow circulation conveyor The innovative air circulation system envelops the food while reducing the time of the cooling cycle.
			
Easy maintenance The quick release system for the front panel allows the condenser battery to be cleaned quickly, ensuring that its performance over time remains constant.	Ventilation panel opening The evaporator is easy to inspect. Its quick release system makes cleaning and maintenance easy.	Slides and racks Racks with positioning holes allow easy repositioning of the slides for EN60x40 and GN1/1 (excluded models L 710 mm).	Core probe Developed with an exclusive ergonomic design, it can be easily dismantled and replaced thanks to a simple connector. Multipoint or heated optional.

Other characteristics

External and internal body is made of steel AISI 304	CFC/HCFC FREE, insulation thickness: 60 mm	Touch screen 4.3" with USB socket	Removable stainless steel racks without the need for tools
Hot gas defrosting (Plug-In), at forced air (Remote)	Variable air flow condenser	Anti-corrosion painted evaporator	Door frame with anti-condensation system
Operates in climate class 5	Connection MODBUS-RT	Cosmo wi-fi supervision system	Plug-In and Remote versions

MODI blast chillers

Up & Active

	Depth 700 mm 5T GN1/1	Depth 700 mm 5T GN1/1 EN60x40	5T GN1/1 EN60x40
			
Size (mm)	L 710 D 700 H 853	L 780 D 700 H 853	L 780 D 800 H 853
Yield per cycle	+90° +3°C	20 Kg	22 Kg
	+90° -18°C	14 Kg	17 Kg
Consumption*	+65° +10°C	0,070 kWh/kg	0,067 kWh/kg
	+65° -18°C	0,265 kWh/kg	0,259 kWh/kg
Total rate	Up	1030W - 5,2A	1030W - 5,2A
	Active	1430W - 7,2A	1430W - 7,2A
Voltage	220/240V-50Hz	220/240V-50Hz	220/240V-50Hz
Equipment	Support with 5 GN1/1 positions	5 slides GN1/1 - EN60x40	5 slides GN1/1 - EN60x40
Versions	Remote Water condensation Special voltage	Remote Water condensation Special voltage	Remote Water condensation Special voltage

Size (mm)	
Yield per cycle	+90° +3°C
	+90° -18°C
Consumption*	+65° +10°C
	+65° -18°C
Total rate	Up
	Active
Voltage	
Equipment	
Versions	

*manual cycle -40°C
Regulations EN 17032:2018
** with top and splashback

3T

GN2/3



NOTE
Model with Hard and Soft
blast chilling and deep
freezing functions

L 625 D 600 H 421
7 Kg
5 Kg
0,076 kWh/kg
0,247 kWh/kg
370W - 1,7A
-
220/240V-50Hz
-
Core probe

Depth 700 mm 6T GN1/1	Depth 700 mm 6T GN1/1 EN60x40	6T GN1/1 EN60x40
		
L 710 D 700 H 913	L 780 D 700 H 913	L 780 D 800 H 913
24 Kg	21 Kg	27 Kg
18 Kg	15 Kg	21 Kg
0,075 kWh/kg	0,081 kWh/kg	0,071 kWh/kg
0,221 kWh/kg	0,258 kWh/kg	0,246 kWh/kg
1270W - 6,2A	1300W - 6,6A	1270W - 6,2A
1670W - 8,5A	1700W - 8,6A	1670W - 8,5A
220/240V-50Hz	220/240V-50Hz	220/240V-50Hz
Support with 6 GN1/1 positions	6 slides GN1/1 - EN60x40	6 slides GN1/1 - EN60x40
Remote Water condensation Special voltage	Remote Water condensation Special voltage	Remote Water condensation Special voltage

Depth 700 mm 7T blast chiller counter

GN1/1
EN60x40



L 1400 D 700 H 950**
34 Kg
24 Kg
0,072 kWh/kg
0,247 kWh/kg
1350W - 6,8A
1950W - 9,9A
220/240V-50Hz
7 slides GN1/1 - EN60x40
Remote Water condensation Special voltage Top without splashback Without top

MODI blast chillers

Up & Active

Depth
700 mm
7T
GN1/1



7T
GN1/1
EN60x40



10T
GN1/1
EN60x40



14T
GN1/1
EN60x40



20TP
GN2/1
EN60x80



20T
GN1/1
EN60x40



20K
Trolley
GN1/1 - EN60x40



Size (mm)	L 710 D 700 H 1093
Yield per cycle	+90° +3°C 32 Kg
	+90° -18°C 22 Kg
Consumption*	+65° +10°C 0,070 kWh/kg
	+65° -18°C 0,231 kWh/kg
Total rate	Up 1350W - 6,83A
	Active 1950W - 9,9A
Voltage	220/240V - 50Hz
Equipment	Support with 7 GN1/1 positions
Versions	Remote Water condensation Special voltage

*manual cycle -40°C
Regulations EN 17032:2018

L 780 D 800 H 1093
34 Kg
24 Kg
0,064 kWh/kg
0,221 kWh/kg
1350W - 6,8A
1950W - 9,9A
220/240V - 50Hz
7 slides GN1/1 - EN60x40
Remote Water condensation Special voltage

L 780 D 800 H 1563
50 Kg
40 Kg
0,082 kWh/kg
0,252 kWh/kg
4120W - 7,3A
5120W - 9,1A
400-415V 3N-50/60Hz
10 slides GN1/1 - EN60x40
Remote Water condensation Special voltage

L 780 D 800 H 1778
70 Kg
56 Kg
0,061 kWh/kg
0,250 kWh/kg
4200W - 7,42A
5200W - 9,2A
400-415V 3N-50/60Hz
14 slides GN1/1 - EN60x40
Remote Water condensation Special voltage

L 1100 D 1045 H 1843
80 Kg
60 Kg
0,085 kWh/kg
0,268 kWh/kg
6450W - 11,4A
7450W - 13,2A
400-415V 3N-50/60Hz
10 slides GN2/1 - EN60x80
Remote Water condensation Special voltage

L 810 D 1015 H 2210
88 Kg
62 Kg
0,087 kWh/kg
0,277 kWh/kg
6150W - 10,9A
7150W - 12,6A
400-415V 3N-50/60Hz
20 slides GN1/1 - EN60x40
Remote H 2085 mm Special voltage

L 810 D 1015 H 2240
88 Kg
62 Kg
0,087 kWh/kg
0,277 kWh/kg
6150W - 10,9A
7150W - 12,6A
400-415V 3N-50/60Hz
-
Remote H 2115 mm Special voltage

Refrigeration cabinets



MASTER & SMART refrigeration cabinets in A class

**A**

Models are produced in 2 depths, 5 widths, 5 temperature ranges, either as Plug-In or remote. Many versions are available so that you can make the most of the space, and keep food for longer. Choose the cabinet that best suits your needs, the common denominators are the same: quality, reliability and high performance and savings.



Cosmo the exclusive Coldline supervision system

Cosmo is an innovative Wi-Fi technology that allows you to connect all your Coldline kitchen appliances, and monitor them from your smartphone. It connects the MASTER and SMART cabinets to a Cosmo HUB (MODI, VISION or LEVTRONIC) and, thanks to the Cosmo app, you can check the operating status of each machine in real time and receive immediate alerts in cases of power cuts or improper use by personnel.



Coldline FSS, a technology which provides an economic and fast service


The enormous energy invested into research and development by Coldline puts it at the forefront of its sector in terms of technology and innovation. Each cabinet is marked with the symbol FSS (Fast Service System) and is equipped with a refrigeration system independent of its body, a feature which ensures huge advantages in terms of flexibility and service. All components are easily accessible for simple and timely intervention.



Reliability and high efficiency

Unlike systems from other companies, Coldline cold storage cabinets position an evaporator inside the compartment, which ensures effective air circulation and the maintenance of a perfect temperature, even in cases where it is subject to heavy use. Thanks to the wide spaces in the compartment, the condenser and compressor are always functioning in optimal conditions, which ensures reliability and efficiency over time.

Coldline




1 Evaporator

2 Compressor

3 Condensing unit

Other systems





MASTER cabinets, open the doors to freshness

Class A saving

All MASTER fridges are equipped with R290 natural gas, which guarantees superior efficiency compared to traditional refrigerant gases.

The class A models ensure energy savings of up to 80% compared to similar devices in lower classes, which gives you an immediate economic advantage and reduces the impact on the environment.

Elegant and refined design

The elegant design with rounded external corners, an easy-to-use control panel with a flush-to-panel keypad and high quality finish gives the MASTER cabinet a solid and refined look.

A model for every need

Models are available with capacities ranging from 350 litres to 1400 litres, with half doors, glass doors, reversible doors, and separate compartments for the conservation of fish and different compartments with 2 or 3 temperatures.

Quality makes a difference

The single bodied structure with an insulation thickness of 75 mm is made of best quality AISI 304 stainless steel. The high efficiency and low consumption compressors completes a framework of excellence making the MASTER cabinet suitable for intense use.

MASTER MARINE

The MASTER MARINE section is made for installation on ships, oil and floating platforms. The excellent refrigeration quality of the MASTER series, combined with its safety specifications, make these cabinets the ideal choice for the marine industry.



MASTER FISH

The MASTER FISH section has been developed for the refrigeration of fresh fish. Temperature ranges and accessories allow you to create the ideal environment for holding delicate food such as molluscs, crustaceans, fish slices and fillets or whole fish.



-6°/+4°C
Keep the fish at the optimum temperature between -6°C and +4°C.



Basins in ABS
The ABS basins collect any liquids ensuring the fish does not come into contact with the water.



Cleaning and hygiene
The diamond shaped base and drain provide easy drainage for holding the cleanliness of the refrigerator.



A close-up, low-angle shot of a refrigerator door. The door is light grey with a dark grey handle. The word 'coldline' is printed in a stylized, dark blue font on the door panel. The lighting creates strong shadows, emphasizing the door's structure and the handle's design.

coldline

SMART cabinets, robust for everyday use

Classe A natural cold air

All SMART refrigerators are equipped with R290 natural gas which guarantees a higher efficiency compared to traditional refrigerant gases. The class A models ensure an energy saving of up to 80% compared to similar devices in lower classes which gives you an immediate economic advantage and reduces the impact on the environment.

Everything under control

The processor automatically maintains the set temperature with the right degree of humidity. The easy-to-use and easy-to-clean control panel is designed to simplify temperature regulation and access of stored data.

Quality and ergonomics

The insulation thickness of 75 mm contributes to its positioning in the best energy class. The handle is designed for greater comfort and to ensure a safe and ergonomic grip.

Best organisation of space

The height of the internal shelves is adjustable to a wide range of positions; it is now possible to improve the organisation of the products so as to have them always at hand.

MASTER & SMART common technology

Distinctive characteristics

MASTER

- A range of 78 models
- Stainless steel handle with a thickness of 2 mm
- Stainless steel evaporator cap
- LED lighting
- RAL customised colouring (optional)



SMART

- A range of 24 models
- PVC handle
- PVC evaporator cap



Common characteristics



Modular base
Allows installation on wheels, feet, fixed or mobile base.



Insulation thickness 75 mm
CFC/HCFC FREE, insulation thickness: 75 mm.



Door locks and door stops
Reversible self-closing doors with 105° stop, equipment key lock.



Replaceable gaskets with high performance insulating
Triple chamber geometry with innovative D7 compound, which produces 35% higher insulation efficiency than traditional models.



Pedal opening system
Facilitates the movements and the insertion of trays and heavy containers. (Optional).



Evaporation at zero cost
The water produced by defrosting evaporates by exploiting the heat dissipated by the refrigeration system.



Intelligent ventilation
The fans stop automatically when the door is opened to avoid the intake of hot air from outside.



Racks
Removable stainless steel racks, without the need for tools.

Other characteristics

Exterior and interior in AISI 304 steel. External back and base, and the technical compartment in galvanized steel

Anti-corrosion painted evaporator

Alarms for signalling when door is open or the temperature is too high

Rounded internal and external corners

Ventilated refrigeration

Connection MODBUS-RT

Door frame with an anti-condensation system (-18° -22°C version)

Hot gas defrosting (Plug-In), off cycle automatic (0°+10°C), electric (Remote)

Cosmo wi-fi supervision system (optional)

Refrigerant gas R290 ecological GWP=3

Operates in climate class 5

Plug-In and Remote versions

MASTER refrigeration cabinets

350 lt



500 lt



600 lt



650 lt



700 lt



Size (mm)
Temperature (°C)
Energy class
Annual consumption (kWh)
Voltage
Equipment
Versions

L 535 D 715 H 2085			
0°+10°	-2°+8°	-18°-22°	-6°+4°
A	A	C	A
205	209	1006	205
220/240V-50Hz			
3 plastic coated shelves GN1/1 3 ABS basins			
Remote Water condensation Glass door Special voltage			

L 630 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
A	A	C
261	266	1310
220/240V-50Hz		
3 plastic coated shelves 42x53 cm		
Remote Water condensation Glass door Special voltage		

L 740 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
A	A	C
295	301	1444
220/240V-50Hz		
3 plastic coated shelves 53x53 cm		
Remote Water condensation Glass door Two half doors Special voltage		

L 810 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
B	B	D
378	385	2093
220/240V-50Hz		
3 plastic coated shelves GN2/1		
Remote Water condensation Glass door Two half doors Special voltage		

L 740 D 815 H 2085			
0°+10°	-2°+8°	-18°-22°	-6°+4°
A	A	C	B
327	335	1609	460
220/240V-50Hz			
3 plastic coated shelves GN2/1 6 ABS basins			
Remote Water condensation Glass door Two half doors Special voltage			

MASTER refrigeration cabinets

1200 lt



1400 lt




Size (mm)
Temperature (°C)
Energy class
Annual consumption (kWh)
Voltage
Equipment
Versions

L 1480 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
B	B	C
553	564	2500
220/240V-50Hz		
6 plastic coated shelves 53x53 cm		
Remote Water condensation Glass doors Four half doors Special voltage Double refrigeration system		


L 1480 D 815 H 2085			
0°+10°	-2°+8°	-18°-22°	-6°+4°
B	B	C	B
644	659	2919	644
220/240V-50Hz			
6 plastic coated shelves GN2/1 12 ABS basins			
Remote Water condensation Glass doors Four half doors Special voltage Double refrigeration system			

Temperature
combinations

2 doors
700 lt



2 / 3 doors
1400 lt



Size (mm)
Temperature (°C)
Voltage
Versions

L 740 D 815 H 2085	
A -2°+8°	B -2+8°
A -2°+8°	B -18-22°
A -6°+4°	B -18-22°
220/240V-50Hz	
Remote Water condensation Special voltage	

L 1480 D 815 H 2085		
A -2°+8°	B -2+8°	
A -2°+8°	B -6+4°	
A -2°+8°	B -18-22°	
A -2°+8°	B -2+8°	C -2+8°
A -2°+8°	B -18°-22°	C -2+8°
A -2°+8°	B -6°+4°	C -2+8°
220/240V-50Hz		
Remote Water condensation Special voltage		

SMART refrigeration cabinets

600 lt



Size (mm)
Temperature (°C)
Energy class
Annual consumption (kWh)
Voltage
Equipment
Versions

L 740 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
A	A	C
295	301	1444
220/240V-50Hz		
3 plastic coated shelves 53x53 cm		
Remote Two half doors Special voltage		

700 lt



L 740 D 815 H 2085		
0°+10°	-2°+8°	-18°-22°
A	A	C
327	335	1609
220/240V-50Hz		
3 plastic coated shelves GN2/1		
Remote Two half doors Special voltage		

1200 lt



L 1480 D 715 H 2085		
0°+10°	-2°+8°	-18°-22°
B	B	C
553	564	2500
220/240V-50Hz		
6 plastic coated shelves 53x53 cm		
Remote Four half doors Special voltage Double refrigeration system		

1400 lt



L 1480 D 815 H 2085		
0°+10°	-2°+8°	-18°-22°
B	B	C
644	659	2919
220/240V-50Hz		
6 plastic coated shelves GN2/1		
Remote Four half doors Special voltage Double refrigeration system		

Roll-In & Pass-Through





Roll-In & Pass-Through cold in motion

Safe refrigeration is combined with the practicality of the stainless steel trolley so that trays and serving dishes can be easily transported: a single front in the Roll-In model; push trolley through the Pass-Through model.

In canteens, industrial cooking complexes and catering companies, the handling of plates and trays plays an important role in the organisation of the work. The Roll-In and Pass-Through refrigeration systems are designed to aid in this task in the best possible way, by reducing service times and improving overall efficiency: normal or glass doors to house 1 or 2 trolleys, containing grids or GN2/1 trays.

Roll-In & Pass-Through technology



Common characteristics



Insulation thickness 75 mm
CFC/HCFC FREE, insulation thickness: 75 mm.



Elegant design
The control panel, with a simple and functional design, and is easy to use.



Lock and door stop
Reversible self-closing doors with 105° stop and lock with key.



High performance sealing
Triple chamber geometry with innovative D7 compound, which produces 35% higher insulation efficiency than traditional models.



Trolley
The Roll-In and Pass-Through models can house GN2/1 measuring
L 598 D 660 H 1630.



Impact protection
Special bumpers protect the internal walls from accidental impacts.



Bottom coated in stainless steel.
The bottom, and access ramp for the trolley is covered in stainless steel AISI 304.



Lighting
LED lamp installed on the upper dashboard.

Other characteristics

Exterior and interior in AISI 304 steel. External back and base, and the technical compartment in galvanized steel

Anti-corrosion painted evaporator

Alarms for signalling when door is open or the temperature is too high

Rounded internal and external corners

Ventilated refrigeration

Connection MODBUS-RT

Condensation automatically evaporates

Hot gas defrosting

Cosmo wi-fi supervision system (optional)

Refrigerant gas R290 ecological GWP=3

Operates in climate class 5

Roll-In & Pass-Through

Roll-In

Pass-Through



Size (mm)
Temperature (°C)
Total rate
Cooling capacity (W)
Voltage
Versions

L 810 D 815 H 2115
-2°+8°
390W - 1,8A
713
220/240V-50Hz
Glass door Special voltage

L 810 D 880 H 2115
-2°+8°
390W - 1,8A
713
220/240V-50Hz
Glass door Special voltage

Roll-In

Pass-Through



L 1620 D 815 H 2115
-2°+8°
390W - 1,8A
713
220/240V-50Hz
Glass doors Special voltage

L 1620 D 880 H 2115
-2°+8°
390W - 1,8A
713
220/240V-50Hz
Glass doors Special voltage

Refrigerated
counters



MASTER & SMART counters: A class

**A**

Coldline counters offer an infinite array of solutions to meet your every need. Reduced consumption and high quality storage make them ideal for any work environment.



Cosmo the exclusive Coldline supervision system

Cosmo is an innovative Wi-Fi technology that allows you to connect all your Coldline kitchen appliances and monitor them from your smartphone. It connects the MASTER and SMART counters to a Cosmo HUB (MODI, VISION or LEVTRONIC) and, thanks to the Cosmo app, you can check the operating status of each machine in real time and receive immediate alerts in cases of power cuts or improper use by personnel.




Coldline FSS, a technology which provides an economic and fast service

Coldline counters are equipped with a refrigeration system independent of the body (Fast Service System), a feature which provides huge advantages for maintenance. All components are easily accessible, allowing for simple and timely interventions.



A constant and uniform level of “cold”

The MASTER and SMART counters maintain a perfectly uniform temperature throughout the compartment, even when the draws are fully loaded. Each HUB cooling system is optimized to increase the shelf life of food by up to 25%.



MASTER counters: a unique design with multiple solutions

All you need

Create your personalised counters by choosing from the infinite solutions offered by the MASTER series. You will be able to organise the kitchen to satisfy your every need, improving convenience and practicality.

Doors and drawers

Each compartment can be configured with stainless steel doors, glass doors and a refrigerated drawer units in both the -2°C to +8°C and -15°C to -22°C versions. The innovative dual air recirculation system ensures maximum refrigeration efficiency and optimal distribution of the cold air, even with a full load.

Engine, right or left side

You can choose the position for the technical compartment, either right or left. The model with the remote refrigeration unit ensures maximum comfort in the workshop. In cases in which there are two counters it is possible to have a common technical compartment.


Reinforced base

The technical compartment is integrated into the structure of the counter. The feet are placed under the reinforced base directly below the technical compartment for extra support.

Customised finish

You can customise your MASTER counter by choosing the colour that best matches the style of your kitchen. The paint is applied to the stainless steel surfaces ensuring long life and impeccable hygiene.

Configuration





SMART counters, solidity for practical and safe use

Solid and resistant body

The SMART body is made of thick steel, making it sturdy and resistant. It is made to be reliable and to last.

Sturdy worktop

The worktop is reinforced with a front and rear edge allowing for easier and more efficient cleaning. The splashback is sealed at the back in order to prevent accumulation of dirt.

Drawers GN1/1

The high capacity draws can be completely extractable, and are designed to be interchangeable, even whilst in use and are adaptable to all future needs. Internal heights: 1/3 = 150 mm; 1/2 = 205 mm; 2/3 = 310 mm.

MASTER & SMART counters technology

Distinctive characteristics



MASTER

The back is made of stainless steel AISI 304
Stainless steel handle, thickness 2 mm
Soundproofed engine compartment, left or right
Plug-In and remote versions available with open base
Versions -2°C to +8°C and -15°C to -22°C
Body height: 650-660-700-710-750-760 mm
Depth: 600-700 mm
Customised finish with RAL paint
Electric socket (optional)



SMART

External back in colaminated steel
PVC handle
Soundproofed engine compartment, only on the right side
Plug-In only version
Versions -2°C to +8°C
Body height: 710 mm
Depth: 700 mm

Common characteristics



Robust worktop
Reinforced top with a rounded front and back edge, sealed at the back to avoid accumulation of dirt.



Removable condensing unit
On slides for inspection and cleaning.



Slides and racks
Removable AISI 304 stainless steel racks and slides, without the need for tools.



Ventilated refrigeration
Ventilated refrigeration creates a perfect uniform temperature in each compartment and draw.



Reinforced drawers
Each compartment can be customised with 1/2 - 1/3 - 2/3, -2°C to +8°C or -15°C to -22°C refrigerated drawers.



Replaceable gaskets with high performance sealing
Triple chamber geometry with innovative D7 compound, which produces 35% higher insulation efficiency than traditional models.



Reinforced base
The modular reinforced base allows installation on wheels, feet, a fixed or mobile base.



Evaporation at zero cost
The water produced by defrosting evaporates by exploiting the heat dissipated by the refrigeration system.

Other characteristics

Exterior and interior in AISI 304 steel.

Anti-corrosion painted evaporator

Connection MODBUS-RT

Rounded internal and external corners

Reversible self-closing doors with 105° stop

Cosmo wi-fi supervision system (optional)

CFC/HCFC FREE, insulation thickness: 60 mm

Hot gas defrosting (Plug-In), electric (Remote)

Refrigerant gas R290 ecological GWP=3

Operates in climate class 5

MASTER counters

Plug-In versions

Depth (mm)
Temperature (°C)
Size* (mm)
Energy class
Annual consumption* (kWh)
Voltage
Equipment
Body height (mm)
Versions

* body height 710 mm with top and splashback

Remote versions

Depth (mm)
Temperature (°C)
Size* (mm)
Voltage
Equipment
Body height (mm)
Versions

* body height 710 mm with top and splashback

1 door



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 820 H 950			
A	C	A	C
409	1036	458	1278
220/240V-50Hz			
1 plastic coated shelf 430x325		1 plastic coated shelf GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

1 door



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 680 H 950			
220/240V-50Hz			
1 plastic coated shelf 430x325		1 plastic coated shelf GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

2 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 1300 H 950			
A	D	A	D
449	1732	527	2135
220/240V-50Hz			
2 plastic coated shelves 430x325		2 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

2 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 1090 H 950			
220/240V-50Hz			
2 plastic coated shelves 430x325		2 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

3 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 1780 H 950			
A	D	A	D
540	2346	616	2891
220/240V-50Hz			
3 plastic coated shelves 430x325		3 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

3 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 1570 H 950			
220/240V-50Hz			
3 plastic coated shelves 430x325		3 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

4 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 2260 H 950			
B	D	B	E
746	3280	836	3642
220/240V-50Hz			
4 plastic coated shelves 430x325		4 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

4 doors



D 600		D 700	
-2°+8°	-15°-22°	-2°+8°	-15°-22°
L 2050 H 950			
220/240V-50Hz			
4 plastic coated shelves 430x325		4 plastic coated shelves GN1/1	
650 - 660 - 700 - 710 - 750 - 760			
Glass door			
Drawers GN 1/2, 1/3, 2/3			
With top - Without top			
Technical compartment on the left side			
Special voltage			

SMART counters

2 doors



Size (mm)	L 1300 D 700 H 950
Temperature (°C)	-2°+8°
Energy class	A
Annual consumption* (kWh)	527
Voltage	220/240V-50Hz
Equipment	2 plastic coated shelves GN1/1
Versions	Drawers GN 1/2, 1/3, 2/3 Without top With top Special voltage

3 doors



Size (mm)	L 1780 D 700 H 950
Temperature (°C)	-2°+8°
Energy class	A
Annual consumption* (kWh)	616
Voltage	220/240V-50Hz
Equipment	3 plastic coated shelves GN1/1
Versions	Drawers GN 1/2, 1/3, 2/3 Without top With top Special voltage

4 doors



Size (mm)	L 2260 D 700 H 950
Temperature (°C)	-2°+8°
Energy class	B
Annual consumption* (kWh)	836
Voltage	220/240V-50Hz
Equipment	4 plastic coated shelves GN1/1
Versions	Drawers GN 1/2, 1/3, 2/3 Without top With top Special voltage

* body height 710 mm with top and splashback



SNACK counters, refrigeration governs the cooking

Under refrigerate, over cook


The portable SNACK counters, with a body height of 490 mm, make it possible to create comfortable and efficient cooking zones with stoves, fryers, pasta cookers and other free-standing cooking appliances. Dimensional modularity, ranging from one to four compartments, makes them suitable for small and large kitchens.

Everything at your fingertips

Creating autonomous work areas allows operators to limit their movements by concentrating all the ingredients in a small space. Fresh or semi-finished foods can be stored in large draws or in compartments with stainless steel doors with temperature ranges of -2°C to +8°C or -15°C to -22°C, with customised finishing using RAL paint chosen by the designer.


SNACK counter technology

SNACK counters with added cooking elements



SNACK counter
Body height 490 mm
2 doors
Plug-In version

Inlaid snack counter in cooking block



SNACK counter
Body height 490 mm
1 door
1 drawer 1/1
2 drawers 1/2
Remote version



Robust worktop
Reinforced surface to support cooking appliances.
Radial front and back edge.
Rounded front and back edges.



Evaporation at zero cost
The water produced by thawing evaporates by exploiting the heat dissipated by the refrigeration system.



Racks and slides
Removable AISI 304 stainless steel racks and slides, without the need for tools.



Ventilated refrigeration
Ventilated refrigeration creates a perfect uniform temperature in each compartment and draw.



Reinforced drawers
Each compartment can be customised with GN1/1 - GN1/2, -2°C to +8°C or -15°C to -22°C refrigerated drawers.



Replaceable gaskets with high performance sealing
Triple chamber geometry with innovative D7 compound, which produces 35% higher insulation efficiency than traditional models.



Reinforced base
The modular reinforced base allows installation on wheels, feet, a fixed or mobile base.



Removable condensing unit
On slides for inspection and cleaning.

Other characteristics

Exterior and interior in AISI 304 steel. Rounded internal and external corners

Anti-corrosion painted evaporator

Reversible self-closing doors with 105° stop

Soundproofed engine compartment, left or right, tailor-made, outflow pipe outlet

Plug-In and Remote versions with open base -2°+8°C e -15°-22°C

Cosmo wi-fi supervision system (optional), connection MODBUS-RT

CFC/HCFC FREE, insulation thickness: 60 mm

Hot gas defrosting (Plug-In), electric (Remote)

Customised finish with RAL colours

Refrigerant gas R290 ecological GWP=3

Operates in climate class 5

SNACK counters

Plug-In versions

Temperature (°C)
Size* (mm)
Energy class
Annual consumption (kWh)
Voltage
Equipment
Versions

* with top

1 door



-2°+8°	-15°-22°
L 820 D 700 H 630	
A	C
356	956
220/240V-50Hz	
1 plastic coated shelf GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

2 doors



-2°+8°	-15°-22°
L 1300 D 700 H 630	
A	D
409	1535
220/240V-50Hz	
2 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

3 doors



-2°+8°	-15°-22°
L 1780 D 700 H 630	
A	D
479	1913
220/240V-50Hz	
3 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

4 doors



-2°+8°	-15°-22°
L 2260 D 700 H 630	
B	E
649	2725
220/240V-50Hz	
4 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

Remote versions

Temperature (°C)
Size* (mm)
Voltage
Equipment
Versions

* with top

1 door




-2°+8°C	-15°-22°
L 680 D 700 H 630	
220/240V-50Hz	
1 plastic coated shelf GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

2 doors



-2°+8°C	-15°-22°
L 1090 D 700 H 630	
220/240V-50Hz	
2 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

3 doors



-2°+8°C	-15°-22°
L 1570 D 700 H 630	
220/240V-50Hz	
3 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	

4 doors



-2°+8°C	-15°-22°
L 2050 D 700 H 630	
220/240V-50Hz	
4 plastic coated shelves GN1/1	
Drawers GN1/1 -1/2 Without top Technical compartment on the left side Special voltage	



Saladette & Prep-Station adds space to your kitchen


The Saladette and Prep-Station counters are practical and allow you to organise space in your kitchen more efficiently.

You can customise the Saladette table by choosing the ideal tray configuration for your business, by selecting the relative sizes and the compartment in which to place the components.

The Prep-Station can be configured with 700 mm (GN) and 800 mm (EN) depths and refrigerated lid for GN1/3 and GN1/6 containers.



Saladette & Prep-Station technology



Saladette characteristics



GN basins
The ingredients are conserved in the refrigerated containers, making the work of the operator much easier, who will have everything at hand.




Customised insertion space for containers
The size of the hole on the surface can be customised, creating a Saladette counter which is suitable for every need.




Cleaning and hygiene
The lid (optional) ensures excellent hygiene standards, allowing food to be stored in pans even over night.

Prep-Station characteristics



GN1/3 or GN 1/6 containers
Specific models are available with refrigerated spaces for GN1/3 or GN1/6 containers.



Surfaces available in steel or granite
The solid and sturdy worktop is made of stainless steel AISI 304 or granite.



Counters with 2 depths
Models available with depths of 700 or 800 mm, adaptable to meet all your needs, and for any kitchen.

Common characteristics

Plug-In and Remote versions.
Soundproofed engine compartment, left or right

Anti-corrosion painted evaporator

CFC/HCFC FREE, insulation thickness: 60 mm

Electric socket situated on the front (optional)

Customised finish with RAL colours

Exterior and interior in AISI 304 steel. Rounded corners

Refrigerant gas R290 ecological GWP=3

Removable condensing unit on slides for inspection and cleaning

Cosmo wi-fi supervision system (optional) connection MODBUS-RT

Operates in climate class 5

Hot gas defrosting (Plug-In), electric (Remote)

Reinforced base for installation on wheels, feet, a fixed or mobile base.


Saladette counters

Plug-In versions


Temperature (°C)	-2°+8°C
Size* (mm)	L 820 D 700 H 950
Voltage	220/240V-50Hz
Equipment	1 plastic coated shelf GN1/1
Body height (mm)	650 - 660 - 700 - 710 - 750 - 760
Versions	Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

* body height 710 mm with top and splashback


1 door




2 doors



3 doors



4 doors



-2°+8°C
L 1300 D 700 H 950
220/240V-50Hz
2 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

-2°+8°C
L 1780 D 700 H 950
220/240V-50Hz
3 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

-2°+8°C
L 2260 D 700 H 950
220/240V-50Hz
4 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

Remote versions


Temperature (°C)	-2°+8°C
Size* (mm)	L 680 D 700 H 950
Voltage	220/240V-50Hz
Equipment	1 plastic coated shelf GN1/1
Body height (mm)	650 - 660 - 700 - 710 - 750 - 760
Versions	Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

* body height 710 mm with top and splashback


1 door




2 doors



3 doors



4 doors



-2°+8°C
L 1090 D 700 H 950
220/240V-50Hz
2 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

-2°+8°C
L 1570 D 700 H 950
220/240V-50Hz
3 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

-2°+8°C
L 2050 D 700 H 950
220/240V-50Hz
4 plastic coated shelves GN1/1
650 - 660 - 700 - 710 - 750 - 760
Drawers GN1/1 - 1/2 Without top With top Technical compartment on the left side Special voltage

Prep-Station counters

Plug-In versions

Depth (mm)
Temperature (°C)
Size* (mm)
Voltage
Equipment
Body height (mm)
Versions

* body height 710 mm

2 doors



D 700	D 800
-2°+8°C	
L 1300 H 1005	L 1450 H 1005
220/240V-50Hz	
2 plastic coated shelves GN1/1	2 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

3 doors



D 700	D 800
-2°+8°C	
L 1780 H 1005	L 2005 H 1005
220/240V-50Hz	
3 plastic coated shelves GN1/1	3 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

4 doors



D 700	D 800
-2°+8°C	
L 2260 H 1005	L 2560 H 1005
220/240V-50Hz	
4 plastic coated shelves GN1/1	4 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

Remote versions

Depth (mm)
Temperature (°C)
Size* (mm)
Voltage
Equipment
Body height (mm)
Versions

* body height 710 mm

2 doors



D 700	D 800
-2°+8°C	
L 1090 H 1005	L 1240 H 1005
220/240V-50Hz	
2 plastic coated shelves GN1/1	2 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

3 doors



D 700	D 800
-2°+8°C	
L 1570 H 1005	L 1795 H 1005
220/240V-50Hz	
3 plastic coated shelves GN1/1	3 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

4 doors



D 700	D 800
-2°+8°C	
L 2050 H 1005	L 2350 H 1005
220/240V-50Hz	
4 plastic coated shelves GN1/1	4 plastic coated shelves EN60x40
700 - 710 - 750 - 760	
Drawers 1/2 - 2/3 - 1/3 Top in granite Container for GN1/6 pans Technical compartment on the left side Special voltage	

Coldline Srl

Via Enrico Mattei, 38
35038 Torreglia
Padova - Italy

+39.049.9903830
info@coldline.it

coldline.it