

Fully equipped, complete series to vacuum pack many different food products of all shapes and dimensions. Boxer table-top models ensure an easy and secure vacuum packaging process. With the unique possiblity to store your settings in the 10-program memory, standard on every Boxer table-top model.



Boxer











"Nothing comes close to the reliability and ease of use of Henkelman's Boxer series."

BOXER 35



PUMP CAPACITY 16 m³/h **MACHINE CYCLE 15-35 sec**

CHAMBER DIMENSIONS 370 x 350 x 150 mm

MACHINE DIMENSIONS

550 x 450 x 405 mm SEAL BAR 350 mm

WEIGHT 52 kg

VOLTAGE 230V-1-50Hz POWER 0.55 kW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/ WIDE SEAL, SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID CONTROL, ACS, GAS FLUSH, 1-2 CUT-OFF SEAL

BOXER 42



PUMP CAPACITY 21 m³/h **MACHINE CYCLE 15-35 sec**

CHAMBER DIMENSIONS

370 x 420 x 180 mm

MACHINE DIMENSIONS 530 x 490 x 440 mm

SEAL BAR 420 mm WEIGHT 64 kg

VOLTAGE 230V-1-50Hz

POWER 0.75 - 1.0 KW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/ WIDE SEAL, SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID CONTROL, ACS, GAS FLUSH, 1-2 CUT-OFF SEAL, 2ND SEAL BAR

Boxer







BOXER 42XL



MACHINE CYCLE 15-35 sec **CHAMBER DIMENSIONS**

460 x 420 x 180 mm

MACHINE DIMENSIONS

615 x 490 x 440 mm

SEAL BAR 420 mm

WEIGHT 72 kg

VOLTAGE 230V-1-50Hz

POWER 0,75 - 1,0 KW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/ WIDE SEAL, SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID CONTROL, ACS, GAS FLUSH, 1-2 CUT-OFF SEAL, 2ND SEAL BAR

BOXER 42XL BI-ACTIVE



PUMP CAPACITY 21 m³/h **MACHINE CYCLE 15-35 sec**

CHAMBER DIMENSIONS

460 x 420 x 120 mm

MACHINE DIMENSIONS

620 x 490 x 450 mm

SEAL BAR 420 mm

WEIGHT 72 kg

VOLTAGE 230V-1-50Hz POWER 0.75 - 1.0 kW

OPTIONS

STANDARD

SOFT AIR

SENSOR CONTROL, LIQUID CONTROL, GAS FLUSH, ACS, ESD (ONLY FOR NON-FOOD)

TIME CONTROL, BI-ACTIVE SEAL.

BOXER 52/62



PUMP CAPACITY 21 m³/h MACHINE CYCLE 15-35 sec **CHAMBER DIMENSIONS**

406 x 520 x 180 mm (B52) 360 x 620 x 180 mm (B62)

MACHINE DIMENSIONS

530 x 700 x 440 mm

SEAL BAR 520 mm (B52).

620 mm (B62)

WEIGHT 81 kg

VOLTAGE 230V-1-50Hz

POWER 0.75 - 1.0 KW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/ WIDE SEAL, SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID CONTROL, ACS, GAS FLUSH, 1-2 CUT-OFF SEAL