

Jumbo

Basic series of table-top models equipped for professional usage, at the best available price. Perfect fit for first time vacuum packaging experiences. Cover your packaging needs. Let Jumbo convince you!



"Compact machine, 'Jumbo' results. Easy to use, easy to clean."

JUMBO 42

Standard



Option



PUMP CAPACITY 16 m³/h
MACHINE CYCLE 20-40 sec
CHAMBER DIMENSIONS
 370 x 420 x 180 mm
MACHINE DIMENSIONS
 530 x 490 x 440 mm
SEAL BAR 420 mm
WEIGHT 58 kg
VOLTAGE 230V-1-50Hz
POWER 0,55 kW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/
 WIDE SEAL (8 MM)

OPTIONS

SENSOR CONTROL, 2ND SEAL BAR

Standard with Double seal. Cut-off and Wide seal are options, available for free.

JUMBO 42XL/42XXL

Standard



Option



PUMP CAPACITY

16 m³/h (J42XL), 21 m³/h (J42XXL)

MACHINE CYCLE

20-40 sec

CHAMBER DIMENSIONS

460 x 420 x 180 mm

MACHINE DIMENSIONS

615 x 490 x 440 mm (J42XL)

615 x 490 x 470 mm (J42XXL)

SEAL BAR

420 mm

WEIGHT

65 kg (J42XL),
 70 kg (J42XXL)

VOLTAGE

230V-1-50Hz

POWER

0,55 kW (J42XL)
 0,75 - 1,0 kW (J42XXL)

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/
 WIDE SEAL (8 MM)

OPTIONS

SENSOR CONTROL, 2ND SEAL BAR

The chamber dimensions listed refer to the usable space in the vacuum chamber (length x width x height). The machine dimensions listed refer to length x width x height. Other voltages available. Textual and printing errors reserved.

Jumbo



MINI JUMBO/JUMBO PLUS

Standard



Option: High lid



PUMP CAPACITY

4 m³/h (MJ), 8 m³/h (JP)

MACHINE CYCLE

25-60 sec (MJ), 15-35 sec (JP)

CHAMBER DIMENSIONS

310 x 280 x 85 mm

MACHINE DIMENSIONS

450 x 335 x 305 mm

SEAL BAR 280 mm

WEIGHT 26 kg (MJ), 32 kg (JP)

VOLTAGE 230V-1-50Hz

POWER 0,30 kW (MJ), 0,40 kW (JP)

STANDARD

TIME CONTROL, DOUBLE/
CUT-OFF SEAL

OPTIONS

SENSOR CONTROL,
HIGH LID (H 130 MM)

JUMBO 30/35

Standard



PUMP CAPACITY

8 m³/h (J30), 16 m³/h (J35)

MACHINE CYCLE

20-40 sec (J30), 15-30 sec (J35)

CHAMBER DIMENSIONS

370 x 350 x 150 mm

MACHINE DIMENSIONS

555 x 450 x 365 mm (J30)

555 x 450 x 405 mm (J35)

SEAL BAR 350 mm

WEIGHT 44 kg (J30), 51 kg (J35)

VOLTAGE 230V-1-50Hz

POWER 0,40 kW (J30), 0,55 kW (J35)

STANDARD

TIME CONTROL, DOUBLE/
CUT-OFF/WIDE SEAL (8 MM)

OPTIONS

SENSOR CONTROL

The chamber dimensions listed refer to the usable space in the vacuum chamber (length x width x height). The machine dimensions listed refer to length x width x height. Other voltages available. Textual and printing errors reserved.

