

TEFCOLD 

Freezers

Ice Cream | Chest | Upright



TEFCOLD

ICE CREAM impulse freezers

Ice cream freezers are offered in 6 different sizes with a diversity of lids. All models are are very well suited for branding. Illuminated display board can be supplied as factory order, and baskets are supplied for all models as standard.



Did you know?

You can find the new NIC-range on pages 116-119.

» Ice Cream Freezers



NIC 100 CP

- Curved sliding lid
- Thermometer
- Inner liner of stucco aluminium
- 4 castors included
- Illuminated display board
- Options:
- Customized decoration
- Dividers



Vertically sliding lid NIC 100



Option: Dividers



Option: Illuminated display board



NIC 200

- Curved sliding lids
- Thermometer
- Inner liner of stucco aluminium
- 4 castors included
- Options:
- Customized decoration
- Illuminated display board
- Dividers



NIC 300

- Curved sliding lids
- Thermometer
- Inner liner of stucco aluminium
- 4 castors included
- Options:
- Customized decoration
- Illuminated display board
- Dividers

Technical specifications

Model	NIC 100	NIC 200	NIC 300	NIC 400	NIC 500
Climate Class	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	130	210	320	435	530
Net Volume, l	115	157	245	334	410
External Dimensions, WxDxH(with wheels)	685x665x940	740x656x1005	1030x650x1005	1320x650x1005	1570x650x1005
Internal Dimensions, WxDxH	516x510x830	600x516x840	860x510x840	1180x510x840	1430x510x840
Doors	1 curved sliding glass	2 curved sliding glass	2 curved sliding glass	2 curved sliding glass	2 curved sliding glass
Shelves/Baskets	-	-	-	-	-
Outer Body	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	N	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	120	150	220	300	400
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	80	63	70	87	122
Net Weight, kg	47	52	62	72	110
Noise Level, dB(A)	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R404a	R404a	R404a	R404a	R404a
Charge, g	130	145	145	155	165
Internal Light	N	N	N	N	N
Option: Charged with R290	Y	Y	Y	Y	Y

» Ice Cream Freezers



NIC 200SC


- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 castors included
- Options:
 - Customized decoration
 - Illuminated display board



Castors with and without brake



Various sizes of baskets available



Option: Illuminated display board



NIC 300SC

- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 castors included
- Options:
 - Customized decoration
 - Illuminated display board



NIC 400SC

- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 castors included
- Options:
 - Customized decoration
 - Illuminated display board

Technical specifications

Model	NIC 200SC	NIC 300SC	NIC 400SC	NIC 500SC
Climate Class	N-T	N-T	N-T	N-T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	211	328	440	539
Net Volume, l	157	245	334	410
External Dimensions, WxDxH(with wheels)	740x650x773	1030x650x773	1320x650x773	1570x650x773
Internal Dimensions, WxDxH	680x510x610	890x510x610	1180x510x610	1430x510x610
Doors	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass
Shelves/Baskets	1	1	2	2
Outer Body	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	220	220	320	420
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	63	76	87	122
Net Weight, kg	52	62	72	110
Noise Level, dbA	45	45	45	45
Type of Cooling	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R404a	R404a	R404a	R404a
Charge, g	110	135	155	165
Internal Light	N	N	N	N
Option: Charged with R290	Y	Y	Y	Y

» Ice Cream Freezers



IC400SC

- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 casters included
- Options: Customized decoration
- Illuminated display board



Castors with and without brake



Various sizes of baskets available



Option: Illuminated display board



IC200SC

- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 casters included
- Options: Customized decoration
- Illuminated display board



IC500SC

- Flat sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 casters included
- Options: Customized decoration
- Illuminated display board

Technical specifications

Model	IC200SC	IC300SC	IC400SC	IC500SC	IC700SC
Climate Class	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	191	296	401	491	670
Net Volume, l	165	255	350	430	620
External Dimensions, WxDxH(with wheels)	720x430x798(892)	1010x530x798(892)	1300x530x798(892)	1550x530x798(892)	2055x530x798(892)
Internal Dimensions, WxDxH	600x310x655	890x410x655	1180x410x655	1430x410x655	1930x410x655
Doors	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass
Shelves/Baskets	1 basket	1 basket	2 baskets	2 baskets	3 baskets
Outer Body	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	218	239	320	325	545
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	52	63	72	80	107
Net Weight, kg	46	56	64	72	101
Noise Level, dbA	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R404a	R404a	R404a
Charge, g	180	190	220	230	270
Internal Light	N	N	N	N	N
Option: Charged with R290	🌱	🌱	🌱	🌱	🌱

» Ice Cream Freezers



IC300SCE

- Angled sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 casters included
- Options: Customized decoration
- Illuminated display board



Castors with and without brake



Various sizes of baskets available



Option: Illuminated display board



IC200SCE

- Angled sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 casters included
- Options: Customized decoration
- Illuminated display board



IC400SCE

- Angled sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 casters included
- Options: Customized decoration
- Illuminated display board

Technical specifications

Model	IC100SCE	IC200SCE	IC300SCE	IC400SCE	IC500SCE
Climate Class	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	100	176	264	352	427
Net Volume, l	85	157	230	325	398
External Dimensions, WxDxH(with wheels)	570x570x890(900/885)	720x615x710(855/840)	1010x615x710(855/840)	1300x615x710(855/840)	1550x615x710(855/840)
Internal Dimensions, WxDxH	420x420x200(190)	600x495x117(110)	890x495x117(110)	1180x495x117(110)	1420x495x117(110)
Doors	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass	2 flat sliding glass
Shelves/Baskets	1 basket	1 basket	1 basket	2 baskets	2 baskets
Outer Body	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	129	216	220	320	325
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	40	54	64	74	80
Net Weight, kg	36,5	49	57	66	72
Noise Level, dB(A)	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R404a	R404a
Charge, g	85	160	190	220	230
Internal Light	N	N	N	N	N
Option: Charged with R290	Y	Y	Y	Y	Y

» Ice Cream Freezers



IC400SCEB

- Curved sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 castors included
- Options: Customized decoration
- Illuminated display board



Castors with and without brake



Various sizes of baskets available



Option: Illuminated display board



IC200SCEB

- Curved sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included
- 4 castors included
- Options: Customized decoration
- Illuminated display board



IC500SCEB

- Curved sliding lids with lock
- Thermometer
- Inner liner of stucco aluminium
- 2 baskets included
- 4 castors included
- Options: Customized decoration
- Illuminated display board

Technical specifications

Model	IC100SCEB	IC200SCEB	IC300SCEB	IC400SCEB	IC500SCEB
Climate Class	N-T	N-T	N-T	N-T	N-T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	100	176	264	352	427
Net Volume, l	85	157	230	325	398
External Dimensions, WxDxH(with wheels)	570x570x890(900/885)	720x615x710(855/949)	1010x615x710(855/949)	1300x615x710(855/949)	1550x615x710(855/949)
Internal Dimensions, WxDxH	420x420x200(400)	600x495x107(110)	890x495x107(110)	1180x495x107(110)	1420x495x107(110)
Doors	2 curved sliding glass	2 curved sliding glass	2 curved sliding glass	2 curved sliding glass	2 curved sliding glass
Shelves/Baskets	1 basket	1 basket	1 basket	2 baskets	2 baskets
Outer Body	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	129	216	220	320	325
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	40	54	64	74	80
Net Weight, kg	36,5	49	57	66	72
Noise Level, dbA	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R404a	R404a
Charge, g	85	160	190	220	230
Internal Light	N	N	N	N	N
Option: Charged with R290	⊕	⊕	⊕	⊕	⊕

» Ice Cream Freezers



ST160

- Flat hinged glass lid
- Inner liner of stucco aluminium
- 1 basket included
- 4 double castors included
- Options: Customized decoration
- Illuminated display board



ST400

- Flat hinged glass lid
- Thermometer
- Inner liner of stucco aluminium
- 1 basket included (As standard)
- 4 double castors included
- Options: Customized decoration
- Illuminated display board

Technical specifications

Model	ST160	ST200	ST300	ST400	ST500	ST700
Climate Class	N	N	N	N	N	N
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	115	174	296	401	691	630
Net Volume, l	105	160	255	350	630	620
External Dimensions, WxDxH	550x550x870	720x720x880	1010x720x880	1300x720x880	1550x720x880	2050x720x880
Internal Dimensions, WxDxH	425x425x795	600x600x805	880x600x805	1180x600x805	1430x600x805	1930x600x805
Doors	1 hinged glass lid	1 hinged glass lid	1 hinged glass lid	1 hinged glass lid	1 hinged glass lid	1 hinged glass lid
Shelves/Baskets	1 basket	1 basket	1 basket	1 basket	1 basket	1 basket
Outer Body	White	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	N	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	130	175	265	330	345	345
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	43	56	65	77	86	115
Net Weight, kg	35	51	58	69	78	105
Noise Level, dB(A)	42	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R404a	R404a	R404a
Charge, g	90	160	190	190	230	270
Internal Light	N	N	N	N	N	N
Option: Charged with R290						

» Ice Cream Freezers



DD420

- Curved sliding lids
- LED light
- Thermometer
- Inner liner powder coated
- 12 dividers included
- 4 castors included
- Options: Customized decoration
- LED illuminated display board



DD240CP

- Flat sliding lids
- Inner liner of stucco aluminium
- 4 dividers included (As standard)
- Heated glass frames
- Internal LED light
- LED illuminated display board
- Options: Customized decoration

Technical specifications

Model	DD420CP	DD240CP
Climate Class	N	N
Temperature Range, °C	-18 to -25	-14 to -22
Gross Volume, l	450	242
Net Volume, l	408	223
External Dimensions, WxDxH(with wheels)	1210x790x1213	1010x677x1245(1417)
Internal Dimensions, WxDxH		890x564x920(960x119x481)
Doors	Double layer curved glass	
Shelves/Baskets	12 dividers	4
Outer Body	White/Grey	White/Grey
Interior	Powder coated	Stucco Aluminium
Castors/Feet	4	4
Lock	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	950	420
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	105	105
Net Weight, kg	95	87
Noise Level dbA	45	45
Type of Cooling	Static	Static
Type of Defrost	Manual	Manual
Controller	Electronic	Mechanical
Thermometer	Y	N
Refrigerant	R134a	R404a
Charge, g	220	220
Internal Light	LED	LED
Canopy Light	LED	LED

CHEST

storage freezers

The chest freezers are available in five different sizes, all with stainless steel lid as option. internal baskets are included in all models.



» Chest Freezers



FR305

- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- 4 castors included
- 1 basket included



FR205

- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- 4 castors included
- 1 basket included



FR605

- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- Internal light
- 3 baskets included
- 4 castors included

Technical specifications

Model	FR205	FR305	FR405	FR505	FR605
Climate Class	T	T	T	T	T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	189	278	385	483	567
Net Volume, l	185	273	377	454	557
External Dimensions, WxDxH	734x700x945	984x700x945	1284x700x945	1594x700x945	1894x700x945
Internal Dimensions, WxDxH	610x480x725	860x480x725	1160x480x725	1380x480x725	1680x480x725
Doors	Solid lid	Solid lid	Solid lid	Solid lid	Solid lid
Shelves/Baskets	1 basket	1 basket	2 baskets	2 baskets	3 baskets
Outer Body	White	White	White	White	White
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 castors	4 castors	4 castors	4 castors	4 castors
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	100	120	150	150	220
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	43	50	59	66	73
Net Weight, kg	36.5	46.5	55	61	68
Noise Level, dBA	42	42	42	42	42
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R600a	R600a	R600a	R600a	R600a
Charge, g	44	50	60	90	105
Internal Light	N	N	10 W	10 W	10 W

» Chest Freezers



FR60SS

- Stainless steel lid
- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- Internal light
- 3 baskets included
- 4 castors included



FR40SS

- Stainless steel lid
- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- 4 castors included
- 2 baskets included



FR50SS

- Stainless steel lid
- Handle with lock
- Defrost water drain
- Thermometer included
- Inner liner of stucco aluminium
- 4 castors included
- 2 baskets included

Technical specifications

Model	FR20SS	FR30SS	FR40SS	FR50SS	FR60SS
Climate Class	T	T	T	T	T
Temperature Range, °C	-14 to -24	-14 to -24	-14 to -24	-14 to -24	-14 to -24
Gross Volume, l	189	278	385	483	567
Net Volume, l	185	273	377	454	557
External Dimensions, WxDxH	734x700x945	986x700x945	1284x700x945	1594x700x945	1804x700x945
Internal Dimensions, WxDxH	610x480x725	860x480x725	1160x480x725	1380x480x725	1680x480x725
Doors	Solid lid, SS	Solid lid, SS	Solid lid, SS	Solid lid, SS	Solid lid, SS
Shelves/Baskets	1 basket	1 basket	2 baskets	2 baskets	3 baskets
Outer Body	White, SS lid	White, SS lid	White, SS lid	White, SS lid	White, SS lid
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 castors	4 castors	4 castors	4 castors	4 castors
Lock	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	100	120	150	150	220
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	43	50	59	66	73
Net Weight, kg	40	47	55	61	68
Noise Level, dBA	42	42	42	42	42
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R600a	R600a	R600a	R600a	R600a
Charge, g	44	50	60	60	105
Internal Light	N	N	N	N	N



» Chest Freezers



- CF700S**
- Stainless steel lid
 - Fast and high freezing capacity
 - Handle with lock
 - Internal light
 - 1 baskets included
 - Control panel with alarm
 - 4 castors, 2 with brake
 - Defrost water drain
 - Service free built-in condenser



- CF700**
- Fast and high freezing capacity
 - Handle with lock
 - Internal light
 - 1 basket included
 - Control panel with alarm
 - 4 castors, 2 with brake
 - Defrost water drain
 - Service free built-in condenser

Technical specifications

Model	CF700	CF700S
Climate Class	T	T
Temperature Range, °C	-14 to -24	-14 to -24
Gross Volume, l	675	675
Net Volume, l	648	648
External Dimensions, WxDxH	2060x716x830	2060x716x830
Internal Dimensions, WxDxH	1935x510x685	1935x510x685
Doors	Solid lid	Solid lid, SS
Shelves/Baskets	1 basket	1 basket
Outer Body	White	White
Interior	Shutco Aluminium	Shutco Aluminium
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y
Voltage/Frequency, V/Hz	230-240/50	230-240/50
Input Power, W	201	201
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	107	107
Net Weight, kg	101	101
Noise Level, dBA	45	45
Type of Cooling	Static	Static
Type of Defrost	Manual	Manual
Controller	Mechanical	Mechanical
Thermometer	Y	Y
Refrigerant	R404a	R404a
Charge, g	290	290
Internal Light	10 W	10 W



UPRIGHT display freezers

The upright freezers UFSC/UFFS are available with solid door or glass door and with or without illuminated canopy. As the bottle coolers, these freezers are suitable for branding.

The smaller UF50/100G merchandising models with glass door can be placed on counters for a better display of products, and are also available with illuminated canopy.



Did you know?

We offer matching coolers for most of our upright freezers. For example, the UFSC/UFFS models match the popular FS/SCU coolers.

See our website or ask the sales team for more information.

» Upright Freezers



NF2500G

- LED illuminated canopy
- Ventilated cooling
- Interior LED light
- Digital temperature display
- 5 adjustable shelves
- Adjustable feet
- Automatic defrost
- Lock
- Self-closing door
- Option: Customized decoration



UFSC1450GCP

- Illuminated canopy
- Fan assisted cooling
- Interior light
- Digital temperature display
- 5 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



NF5000G

- LED illuminated canopy
- Ventilated cooling
- Interior LED light
- Digital temperature display
- 10 adjustable shelves
- Adjustable feet
- Automatic defrost
- Lock
- 2 Self-closing doors
- Option: Customized decoration

Technical specifications

Model	NF2500G	NF5000G	UFFS1450GCP	UFSC1450GCP
Climate Class	N	N	N	N
Temperature Range, °C	-12 - 24	-12 - 24	-12 to -22	-12 to -22
Gross Volume, l	444	994	480	480
Net Volume, l	412	930	353	353
External Dimensions, WxDxH	680x720x1990	1270x720x1990	680x695x2090	680x695x2090
Internal Dimensions, WxDxH	580x620x1270	1250x620x1270	577x620x1664	577x620x1664
Doors	1 self closing glass	2 self closing glass	1 glass	1 glass
Shelves/Baskets	5 adjustable	10 adjustable	6	6
Outer Body	White	White	White	White
Interior	Coated steel	Coated steel	Aluminium	Aluminium
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	100	110	90	90
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	149	242	130	130
Net Weight, kg	138	227	117	117
Noise Level dbA	48	48	48	48
Type of Cooling	Ventilated	Ventilated	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Manual	Manual
Controller	Digital	Digital	Mechanical	Mechanical
Thermometer	Y	Y	Y	Y
Refrigerant	R404a	R404a	R404a	R404a
Charge, g	480	880	325	325
Internal Light	LED	LED	38 W Neon	38 W Neon
Canopy Light	LED	LED	18 W Neon	18 W Neon

» Upright Freezers



UFFS370GCP

- Illuminated canopy
- Fan assisted cooling
- Interior light
- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



UFFS370G

- Fan assisted cooling
- Interior light
- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



UFFS370SD

- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration

Technical specifications

Model	UFFS370G	UFFS370GCP	UFFS370SD
Climate Class	N	N	N
Temperature Range, °C	-12 to -23	-12 to -23	-14 to -24
Gross Volume, l	300	300	300
Net Volume, l	270	270	270
External Dimensions, WxDxH	595x440x1840	595x440x1840	595x440x1840
Internal Dimensions, WxDxH	470x440x1545	470x440x1545	470x440x1545
Doors	1 glass	1 glass	1 solid
Shelves/Baskets	6 fixed freezing	6 fixed freezing	6 fixed freezing
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	570	570	270
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	94	97	85.5
Net Weight, kg	86	89	80
Noise Level, dB(A)	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Static
Type of Defrost	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R404a	R404a	R404a
Charge, g	190	190	190
Internal Light	15 W Neon	15 W Neon	N
Canopy Light	N	15 W Neon	N

» Upright Freezers



UFSC370SD

- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



UFSC370G

- Fan assisted cooling
- Interior light
- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



UFSC370GCP

- Illuminated canopy
- Fan assisted cooling
- Interior light
- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration

Technical specifications

Model	UFSC370G	UFSC370GCP	UFSC370SD
Climate Class	N	N	N
Temperature Range, °C	-12 to -23	-12 to -23	-14 to -24
Gross Volume, l	300	300	300
Net Volume, l	270	270	270
External Dimensions, WxDxH	595x440x1840	595x440x1840	595x440x1840
Internal Dimensions, WxDxH	470x440x1545	470x440x1545	470x440x1545
Doors	1 glass	1 glass	1 solid
Shelves/Baskets	6 fixed freezing	6 fixed freezing	6 fixed freezing
Outer Body	White	White	White
Interior	ABS	ABS	ABS
Castors/Feet	2 adjustable feet	2 adjustable feet	2 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	570	570	270
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	94	97	85.5
Net Weight, kg	86	89	80
Noise Level, dB(A)	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Static
Type of Defrost	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical
Thermometer	Y	Y	Y
Refrigerant	R404a	R404a	R404a
Charge, g	190	190	190
Internal Light	15 W Neon	15 W Neon	N
Canopy Light	N	15 W Neon	N

» Upright Freezers



UF100G

- Interior LED light
- Self-closing tripple glazed door
- 3 Adjustable shelves
- Adjustable feet
- Aluminium interior
- Lock
- Replaceable door gasket



UF50GCP

- LED illuminated canopy
- Interior LED light
- Self-closing tripple glazed door
- 2 Adjustable shelves
- Adjustable feet
- Aluminium interior
- Lock
- Replaceable door gasket



UF100GCP

- LED illuminated canopy
- Interior LED light
- Self-closing tripple glazed door
- 3 Adjustable shelves
- Adjustable feet
- Aluminium interior
- Lock
- Replaceable door gasket

Technical specifications

Model	UF50G	UF50GCP	UF100G	UF100GCP
Climate Class	N	N	N	N
Temperature Range, °C	-12 - -24	-12 - -24	-12 - -24	-12 - -24
Gross Volume, l	50	50	90	118
Net Volume, l	48	48	88	113
External Dimensions, WxDxH	570x320x320	570x320x327	610x440x370	610x455x380
Internal Dimensions, WxDxH	430x270x280	430x270x280	500x350x340	500x350x340
Doors	1 self closing glass	1 self closing glass	1 self closing glass	1 self closing glass
Shelves/Baskets	2 coated	2 coated	3 coated	3 coated
Outer Body	White	White	White	White
Interior	Stainless Aluminium	Stainless Aluminium	Stainless Aluminium	Stainless Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	154	154	220	220
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	45	49	54	58
Net Weight, kg	40	44	49	53
Noise Level, dB(A)	45	45	45	45
Type of Cooling	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Mechanical	Mechanical
Thermometer	N	N	N	N
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	110	110	135	135
Internal Light	LED	LED	LED	LED
Canopy Light	N	LED	N	LED

» Upright Freezers



UF200S

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 Fixed shelves
- Adjustable feet at front, rollers at back
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs



UF400

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed freezing shelves
- Adjustable feet at front, rollers at back
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs



UF400S

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed shelves
- Adjustable feet at front, rollers at back
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs

Technical specifications

Model	UF200	UF200S	UF400	UF400S
Climate Class	N	N	N	N
Temperature Range, °C	-10 to -24	-10 to -24	-10 to -24	-10 to -24
Gross Volume, l	200	200	400	400
Net Volume, l	120	120	340	340
External Dimensions, WxDxH	600x600x850	600x600x850	600x600x1850	600x600x1850
Internal Dimensions, WxDxH				
Doors	1 solid White	1 solid SS400	1 solid White	1 solid SS400
Shelves/Baskets	3 fixed freezing	3 fixed freezing	7 fixed freezing	7 fixed freezing
Outer Body	White	SS400	White	SS400
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	230-240/50	230-240/50	230-240/50	230-240/50
Input Power, W	150	150	210	210
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	50	50	79	79
Net Weight, kg	45	45	74	74
Noise Level, dbA	40	40	40	40
Type of Cooling	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	75	75	185	185
Internal Light	N	N	N	N

» Upright Freezers



BA10UF

- Interior LED light
- Fan assisted cooling
- Aluminium door frame
- Double glazed door
- 2 adjustable shelves
- Adjustable feet
- Digital thermometer



UF200G

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 fixed freezing shelves
- Adjustable feet at front, rollers at back
- Digital thermometer
- Option: Wheels or adjustable legs



UF400SG

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 fixed freezing shelves
- Adjustable feet at front, rollers at back
- Digital thermometer
- Option: Wheels or adjustable legs

Technical specifications

Model	BA10UF	BA15UF	UF200G	UF200SG	UF400G	UF400SG
Climate Class	N	N	N	N	N	N
Temperature Range, °C	-22 to -14	-22 to -14	-10 to -24	-10 to -24	-10 to -24	-10 to -24
Gross Volume, l	124	122	200	200	600	600
Net Volume, l	118	116	120	120	340	340
External Dimensions, WxDxH	600x532x900	600x526x970	600x490x950	600x490x950	600x900x1850	600x900x1850
Internal Dimensions, WxDxH	508x355x732	508x355x720	484x376x723	484x376x723	480x870x1695	480x870x1695
Doors	1 hinged glass	1 hinged glass	1 hinged glass	1 hinged glass	1 hinged glass	1 hinged glass
Shelves/Baskets	2, 496x350	2, 496x350	3 fixed freezing	3 fixed freezing	7 fixed freezing	7 fixed freezing
Outer Body	Black	Black	White	S5430	White	S5430
Interior	Stucco Aluminium	Stucco Aluminium	ABS	ABS	ABS	ABS
Castors/Feet	4 adjustable feet	4 adjustable feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	210	210	150	150	210	210
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	49	49	55	55	84	84
Net Weight, kg	47	47	49	49	79	79
Noise Level, dB(A)	45	45	42	42	42	42
Type of Cooling	Ventilated assisted	Ventilated assisted	Static	Static	Static	Static
Type of Defrost	Automatic	Automatic	Manual	Manual	Manual	Manual
Controller	Mechanical	Mechanical	Digital	Digital	Digital	Digital
Thermometer	N	N	Y	Y	Y	Y
Refrigerant	R404a	R404a	R404a	R404a	R404a	R404a
Charge, g	130	130	75	75	185	185
Internal Light	LED	LED	LED	LED	LED	LED

» Upright Freezers



UF550S

- Digital temperature display
- 6 fixed freezing shelves
- Adjustable feet
- Defrost water drain
- Lock
- Replaceable door gasket
- Option: Customized decoration



UF600S

- Stainless steel exterior
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed freezing shelves
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs



UF700V

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 adjustable shelves, 1 bottom shelf
- Ventilated cooling
- Digital thermometer
- 4 wheels

Technical specifications

Model	UF550	UF550S	UF600	UF600S	UF700V	UF700VS
Climate Class	N	N	N	N	N	N
Temperature Range, °C	-10 to -24	-10 to -24	-10 to -24	-10 to -24	-10 to -24	-10 to -24
Gross Volume, l	461	461	600	600	641	641
Net Volume, l	420	420	555	555	550	550
External Dimensions, WxDxH	777x726x1720	777x726x1720	770x750x1900	770x750x1900	777x726x1970	777x726x1970
Internal Dimensions, WxDxH	600x551x1400	600x551x1400	650x580x1600	650x580x1600	600x581x1600	600x581x1600
Doors	1 solid White	1 solid SS430	1 solid White	1 solid SS430	1 solid White	1 solid SS430
Shelves/Baskets	7 fixed freezing	7 fixed freezing	7 fixed freezing, GN2/1	7 fixed freezing, GN2/1	3 adjustable GN2/1	3 adjustable GN2/1
Outer Body	White	White	White	White	White	White
Interior	ABS	ABS	ABS	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	4 wheels	4 wheels
Lock	Y	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	250	250	240	240
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	92	92	101	101	122	122
Net Weight, kg	85	85	94	94	113	113
Noise Level, dB(A)	45	45	45	45	45	45
Type of Cooling	Static	Static	Static	Static	Ventilated	Ventilated
Type of Defrost	Manual	Manual	Manual	Manual	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R404a	R404a
Charge, g	200	200	290	290	350	350
Internal Light	N	N	N	N	N	N