

TEFCOLD   
Cool Products Worldwide

 Gastroline



# GASTROLINE stainless steel

The Tefcold Gastroline range is produced with focus on high quality steel and easy maintenance and offers a wide diversity of options. When it comes to the quality of steel, which is in direct contact with food, we do not compromise. Only the best quality AISI 304 is accepted, because it will last for years - even in the busiest professional kitchens.

Blast chillers for a fast and hygienic cooling of food in professional kitchens can be found on page 198-199 in different sizes.

Pizza Tables produced with granite table top are offered in many different sizes, with or without drawers. Several models are equipped with refrigerated topping units.

The Saladette range is suitable for Gastronorm pans, and is available with or without hinged lid and saladette well. The Sandwich Table range accepts Gastronorm pans in the refrigerated topping section. Drawers are offered as option, and glass structures for protection/display of food can be supplied for some of the models.

The Upright range offers a variety of options for combining matching Refrigerators and Freezers. Standard cabinets as well as special cabinets for storage of ice cream or fish are offered. Several products are available with glass doors or with double- or half-doors.

The Chilled Topping Units are offered in different sizes suitable for any purpose. Each model accepts Gastronorm pans and is delivered with either glass structure for better display and protection of toppings or with stainless steel lid.



### Did you know?

Both Gastronorm and Euronorm standard counters and cabinets are available on the following pages.

## » Snack Freezer / Chiller



### RF500 SNACK

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 adjustable shelves
- 4 adjustable feet
- Static cooling
- Digital thermometer



Bottom shelf available



### RK500 SNACK

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable shelves
- 4 adjustable feet
- Fan assisted cooling
- Automatic defrost
- Digital thermometer



### RKS600 FISH

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 8 trays for fish
- 4 castors, 2 with brake
- Static cooling
- Manual defrost
- Digital thermometer
- Option: Adjustable legs

### Technical specifications

| Model                       | RF500 SNACK  | RK500 SNACK  | RKS600 FISH  |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | -10 to -20   | -2 to 8  | -8 to 8  |
| Gross Volume, l             | 450  | 450  | 560  |
| Net Volume, l               | 429  | 429  | 507  |
| External Dimensions, WxDxH  | 660x700x1900   | 660x700x1900   | 660x810x2010   |
| Internal Dimensions, WxDxH  | 600x530x1300   | 600x530x1300   | 600x630x1300   |
| Doors                       | 1 self closing solid                                   | 1 self closing solid                                   | 1 self closing solid                                   |
| Shelves/Baskets             | 3  | 3  | 8 trays  |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable feet                                      | 4 adjustable feet                                      | 2 with, 2 without brake                                |
| Lock                        | Y  | Y  | Y  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 600  | 300  | 450  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 140  | 140  | 145  |
| Net Weight, kg              | 130  | 130  | 135  |
| Noise Level, dB(A)          | 42   | 42   | 40   |
| Type of Cooling             | Static   | Fan assisted   | Static   |
| Type of Defrost             | Manual   | Automatic  | Manual   |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R404a  | R134a  | R134a  |
| Charge, g                   | 390  | -  | -  |
| Internal Light              | N  | N  | N  |

## » Upright Freezer / Chiller



### RK505

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable shelves
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer



### RK1010

- Stainless steel exterior
- Lock fitted as standard
- 2 self-closing doors
- 6 Adjustable shelves
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer

### Technical specifications

| Model                       | RF505  | RF1010   | RK505  | RK1010   |
|-----------------------------|--|--|--|--|
| Climate Class, N, SN, ST    | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | -18 to -24   | -18 to -24   | -2 to 8  | -2 to 8  |
| Gross Volume, l             | 466  | 976  | 466  | 976  |
| Net Volume, l               | 429  | 900  | 429  | 900  |
| External Dimensions, WxDxH  | 660x710x2010   | 1340x710x2010  | 660x710x2010   | 1340x710x2010  |
| Internal Dimensions, WxDxH  | 600x650x1380   | 1220x650x1380  | 600x650x1380   | 1220x650x1380  |
| Doors                       | 1 solid SS304  | 2 solid SS304  | 1 solid SS304  | 2 solid SS304  |
| Shelves/Baskets             | 3 coated steel   | 6 coated steel   | 3 coated steel   | 6 coated steel   |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Feet                | 2 with, 2 without brake                                | 2 with, 2 without brake                                | 2 with, 2 without brake                                | 2 with, 2 without brake                                |
| Lock                        | Y  | Y  | Y  | Y  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 160  | 160  | 300  | 160  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 145  | 195  | 145  | 195  |
| Net Weight, kg              | 135  | 180  | 135  | 180  |
| Noise Level db(A)           | 45   | 45   | 45   | 45   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R404a  | R404a  | R134a  | R134a  |
| Charge, g                   | 390  | 500  | 210  | 320  |
| Internal Light              | N  | N  | N  | N  |



## » Upright freezer / Chiller GN2/1



Kits for Euronorm available



Castor with brake

### RK710G

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing glass door
- 3 Adjustable GN2/1 shelves
- Interior light
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs



### RF710

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable GN2/1 shelves
- Interior light
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs



### RK1420

- Stainless steel exterior
- Lock fitted as standard
- 2 self-closing doors
- 6 Adjustable GN2/1 shelves
- Suitable for fresh meat (-2/+2)
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs

### Technical specifications

| Model                       | RF710                   | RF1420                  | RK710                   | RK1420                  | RK710G                  | RK1420G                 |
|-----------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Climate Class               | ST                      | ST                      | ST                      | ST                      | ST                      | ST                      |
| Temperature Range, °C       | -18 to -24              | -18 to -24              | -2 to 10                | -2 to 10                | -2 to 10                | -2 to 10                |
| Gross Volume, l             | 650                     | 1410                    | 650                     | 1410                    | 650                     | 1410                    |
| Net Volume, l               | 597                     | 1325                    | 597                     | 1325                    | 597                     | 1325                    |
| External Dimensions, WxDxH  | 740x850x2010            | 1480x850x2010           | 740x850x2010            | 1480x850x2010           | 740x850x2010            | 1480x850x2010           |
| Internal Dimensions, WxDxH  | 624x695x1396            | 1300x695x1396           | 624x695x1396            | 1300x695x1396           | 624x695x1396            | 1300x695x1396           |
| Doors                       | 1 self closing solid    | 2 self closing solid    | 1 self closing solid    | 2 self closing solid    | 1 self closing glass    | 2 self closing glass    |
| Shelves/Baskets             | 3, GN2/1                | 6, GN2/1                | 3, GN2/1                | 6, GN2/1                | 3, GN2/1                | 6, GN2/1                |
| Outer Body                  | SS304                   | SS304                   | SS304                   | SS304                   | SS304                   | SS304                   |
| Interior                    | SS304                   | SS304                   | SS304                   | SS304                   | SS304                   | SS304                   |
| Castors/Feet                | 2 with, 2 without brake | 2 with, 2 without brake | 2 with, 2 without brake | 2 with, 2 without brake | 2 with, 2 without brake | 2 with, 2 without brake |
| Lock                        | Y                       | Y                       | Y                       | Y                       | Y                       | Y                       |
| Voltage/Frequency, V/Hz     | 220-240/50              | 220-240/50              | 220-240/50              | 220-240/50              | 220-240/50              | 220-240/50              |
| Input Power, W              | 1000                    | 1200                    | 450                     | 650                     | 450                     | 650                     |
| Energy Consumption, kWh/24h | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      |
| Gross Weight, kg            | 147                     | 220                     | 143                     | 213                     | 143                     | 213                     |
| Net Weight, kg              | 138                     | 198                     | 134                     | 198                     | 134                     | 198                     |
| Noise Level, dB(A)          | 48                      | 48                      | 48                      | 48                      | 48                      | 48                      |
| Type of Cooling             | Ventilated              | Ventilated              | Ventilated              | Ventilated              | Ventilated              | Ventilated              |
| Type of Defrost             | Automatic               | Automatic               | Automatic               | Automatic               | Automatic               | Automatic               |
| Controller                  | Digital                 | Digital                 | Digital                 | Digital                 | Digital                 | Digital                 |
| Thermometer                 | Y                       | Y                       | Y                       | Y                       | Y                       | Y                       |
| Refrigerant                 | R404a                   | R404a                   | R134a                   | R134a                   | R134a                   | R134a                   |
| Charge, g                   | 460                     | 500                     | 300                     | 500                     | 300                     | 500                     |
| Internal Light              | 25 W                    | 2x25 W                  | 25 W                    | 2x25 W                  | 25 W                    | 2x25 W                  |



## » Upright Freezer / Chiller



### UF550S

- Stainless steel exterior
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed shelves
- Adjustable feet
- Static cooling
- Digital thermometer
- Option: Baskets



### UR550S

- Stainless steel cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves
- Fan assisted cooling
- Automatic defrost
- Digital thermometer



### UF550

- White exterior
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed shelves
- Adjustable feet
- Static cooling
- Digital thermometer
- Option: Baskets

### Technical specifications

| Model                       | UR550  | UR550S   | UF550  | UF550S   |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 0 to 10  | 0 to 10  | -10 to -24   | -10 to -24   |
| Gross Volume, l             | 461  | 461  | 461  | 461  |
| Net Volume, l               | 420  | 420  | 406  | 406  |
| External Dimensions, WxDxH  | 777x726x1720   | 777x726x1720   | 777x726x1720   | 777x726x1720   |
| Internal Dimensions, WxDxH  | 600x555x1460   | 600x555x1460   | 600x555x1460   | 600x555x1460   |
| Doors                       | 1 solid white  | 1 solid SS430  | 1 solid white  | 1 solid SS430  |
| Shelves/Baskets             | 4 adjustable   | 4 adjustable   | 7 fixed freezing                                       | 7 fixed freezing                                       |
| Outer Body                  | White  | SS430  | White  | SS430  |
| Interior                    | ABS  | ABS  | ABS  | ABS  |
| Castors/Feet                | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   |
| Lock                        | Y  | Y  | Y  | Y  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 250  | 250  | 250  | 250  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 92   | 92   | 92   | 92   |
| Net Weight, kg              | 85   | 85   | 85   | 85   |
| Noise Level, dB(A)          | 45   | 45   | 45   | 45   |
| Type of Cooling             | Static   | Static   | Static   | Static   |
| Type of Defrost             | Automatic  | Automatic  | Manual   | Manual   |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | 200  | 200  | 200  | 200  |
| Internal Light              | N  | N  | N  | N  |



## » Upright freezer / Chiller GN2/1



### UR600S

- Stainless steel exterior
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves GN2/1
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs



### UF600

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed shelves GN2/1
- Adjustable feet at front, rollers at back
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs



### UR600

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves GN2/1
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs

### Technical specifications

| Model                       | UF600  | UF600S   | UR600  | UR600S   |
|-----------------------------|--|--|--|--|
| Climate Class               | N  | N  | N  | N  |
| Temperature Range, °C       | -10 to -24   | -10 to -24   | 0 to 10  | 0 to 10  |
| Gross Volume, l             | 655  | 655  | 655  | 655  |
| Net Volume, l               | 555  | 555  | 570  | 570  |
| External Dimensions, WxDxH  | 770x750x1900   | 770x750x1900   | 770x750x1900   | 770x750x1900   |
| Internal Dimensions, WxDxH  | 653x300x1600   | 653x300x1600   | 653x300x1600   | 653x300x1600   |
| Doors                       | 1 solid White  | 1 solid SS430  | 1 solid White  | 1 solid SS430  |
| Shelves/Baskets             | 7 fixed freezing, GN2/1                                | 7 fixed freezing, GN2/1                                | 3, GN2/1 and 1, 650x305                                | 3, GN2/1 and 1, 650x305                                |
| Outer Body                  | White  | SS430  | White  | SS430  |
| Interior                    | ABS  | ABS  | ABS  | ABS  |
| Castors/Foot                | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   | 2 rollers and 2 feet                                   |
| Lock                        | Y  | Y  | Y  | Y  |
| Voltage/Frequency, V/Hz     | 230-240/50   | 230-240/50   | 230-240/50   | 230-240/50   |
| Input Power, W              | 250  | 250  | 250  | 250  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 191  | 191  | 97   | 97   |
| Net Weight, kg              | 94   | 94   | 90   | 90   |
| Noise Level, dB(A)          | 40   | 40   | 40   | 40   |
| Type of Cooling             | Static   | Static   | Fan assisted   | Fan assisted   |
| Type of Defrost             | Manual   | Manual   | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | 290  | 290  | 210  | 210  |
| Internal Light              | N  | N  | N  | N  |

## » Upright freezer / Chiller GN2/1



### UR700V

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 Adjustable shelves GN2/1
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- 4 wheels



### UF700V

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 3 Adjustable shelves GN2/1
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- 4 wheels

### Technical specifications

| Model                       | UF700V   | UF700VS  | UR700V   | UR700VS  |
|-----------------------------|--|--|--|--|
| Climate Class               | N  | N  | N  | N  |
| Temperature Range, °C       | -10 to -24   | -10 to -24   | -10 to -24   | -10 to -24   |
| Gross Volume, l             | 641  | 641  | 641  | 641  |
| Net Volume, l               | 550  | 550  | 550  | 550  |
| External Dimensions, WxDxH  | 77x720x1970  | 77x720x1970  | 77x720x1970  | 77x720x1970  |
| Internal Dimensions, WxDxH  | 663x511x1660   | 663x511x1660   | 663x511x1660   | 663x511x1660   |
| Doors                       | 1 solid White  | 1 solid SS430  | 1 solid White  | 1 solid SS430  |
| Shelves/Baskets             | 3 adjustable GN2/1                                     | 3 adjustable GN2/1                                     | 3 adjustable GN2/1                                     | 3 adjustable GN2/1                                     |
| Outer Body                  | White  | White  | White  | White  |
| Interior                    | ABS  | ABS  | ABS  | ABS  |
| Castors/Feet                | 4 wheels   | 4 wheels   | 4 wheels   | 4 wheels   |
| Lock                        | Y  | Y  | Y  | Y  |
| Voltage/Frequency, V/Hz     | 230-240/50   | 230-240/50   | 230-240/50   | 230-240/50   |
| Input Power, W              | 50   | 50   | 50   | 50   |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 122  | 122  | 113  | 113  |
| Net Weight, kg              | 113  | 113  | 105  | 105  |
| Noise Level, dB(A)          | 45   | 45   | 45   | 45   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R404a  | R404a  | R134a  | R134a  |
| Charge, g                   | 350  | 350  | 300  | 300  |
| Internal Light              | N  | N  | N  | N  |



## » Gastronorm Counters GN1/1


**CK7210**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Splashback fitted as standard
- Removable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching freezer available



Available without splash back



Set of 2 drawers as separate kit



Set of 3 drawers as separate kit


**CK7410**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 4 self-closing doors
- Splashback fitted as standard
- Removable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching freezer available

### Technical specifications

| Model                       | CK7210   | CK7310   | CK7410   |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | -2 to 10   | -2 to 10   | -2 to 10   |
| Gross Volume, l             | 292  | 417  | 553  |
| Net Volume, l               | 272  | 402  | 533  |
| External Dimensions, WxDxH  | 1360x700x950   | 1795x700x950   | 2230x700x950   |
| Internal Dimensions, WxDxH  | 902x530x589  | 1237x530x589   | 1772x530x589   |
| Doors                       | 2 solid  | 3 solid  | 4 solid  |
| Shelves/Baskets             | 2, GN1/1   | 2, GN1/1   | 3, GN1/1   |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      | 6 adjustable legs                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 280  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 198  | 149  | 173  |
| Net Weight, kg              | 98   | 134  | 153  |
| Noise Level, dB(A)          | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 230  | 230  | 250  |
| Internal Light              | N  | N  | N  |



## » Gastronorm Counters GN1/1


**CK7210G**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing glass doors
- Internal LED light
- Removable table top
- Adjustable legs
- Digital temperature display


**CK7310G**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing glass doors
- Internal LED light
- Removable table top
- Adjustable legs
- Digital temperature display

### Technical specifications

| Model                       | CK7210G  | CK7310G  | CK7410G  |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 292  | 417  | 553  |
| Net Volume, l               | 272  | 402  | 533  |
| External Dimensions, WxDxH  | 1360x700x850   | 1795x700x850   | 2230x700x850   |
| Internal Dimensions, WxDxH  | 900x530x589  | 1237x530x589   | 1772x530x589   |
| Doors                       | 2 glass  | 3 glass  | 4 glass  |
| Shelves/Baskets             | 2, GN1/1   | 3, GN1/1   | 4, GN1/1   |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      | 6 adjustable legs                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 280  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 118  | 164  | 193  |
| Net Weight, kg              | 108  | 149  | 173  |
| Noise Level dB(A)           | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 230  | 230  | 250  |
| Internal Light              | LED  | LED  | LED  |

## » Gastronorm Counters GN1/1



**CF7210**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Splashback fitted as standard
- Removable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching chiller available



Castors as option



Available without splash back



**CF7310**

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing doors
- Splashback fitted as standard
- Removable table top
- Adjustable legs
- Digital temperature display
- Matching chiller available

### Technical specifications

| Model                       | CF7210   | CF7310   | CF7410   |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | -10 to -20   | -10 to -20   | -10 to -20   |
| Gross Volume, l             | 282  | 417  | 553  |
| Net Volume, l               | 272  | 402  | 533  |
| External Dimensions, WxDxH  | 1360x700x950   | 1795x700x950   | 2230x700x950   |
| Internal Dimensions, WxDxH  | 902x530x589  | 1237x530x589   | 1772x530x589   |
| Doors                       | 2 solid  | 3 solid  | 4 solid  |
| Shelves/Baskets             | 2, GN1/1   | 3, GN1/1   | 4, GN1/1   |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      | 6 adjustable legs                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 700  | 700  | 700  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 150  | 185  | 180  |
| Net Weight, kg              | 140  | 150  | 160  |
| Noise Level, dB(A)          | 45   | 45   | 45   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R404a  | R404a  | R404a  |
| Charge, g                   | 300  | 300  | 300  |
| Internal Light              | N  | N  | N  |

## » Snack Counters



**SK6210**

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- 2 shelves
- Splashback as option
- Removable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits



Set of 2 drawers as separate kit



Set of 3 drawers as separate kit



Castors as option



**SK6410**

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 4 self-closing doors
- 4 shelves
- Splashback as option
- Removable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits

### Technical specifications

| Model                       | SK6210   | SK6310   | SK6410   |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | -2 to 10   | -2 to 10   | -2 to 10   |
| Gross Volume, l             | 260  | 360  | 460  |
| Net Volume, l               | 230  | 345  | 460  |
| External Dimensions, WxDxH  | 1360x400x850   | 1795x400x850   | 2230x400x850   |
| Internal Dimensions, WxDxH  | 902x330x589  | 1237x330x589   | 1772x330x589   |
| Doors                       | 2 solid  | 3 solid  | 4 solid  |
| Shelves/Baskets             | 2, 328x430   | 3, 328x430   | 4, 328x430   |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      | 6 adjustable legs                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 260  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 98   | 135  | 143  |
| Net Weight, kg              | 88   | 120  | 123  |
| Noise Level, dB(A)          | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 230  | 230  | 250  |
| Internal Light              | N  | N  | N  |



## » Euronorm Bakery Counters



### BK210

- Euronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- 2 shelves
- Removable table top
- Adjustable legs
- Digital temperature display



Set of 2 drawers as separate kit



Lock for compressor department



Castors as option



### BK310

- Euronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing doors
- 3 shelves
- Removable table top
- Adjustable legs
- Digital temperature display

### Technical specifications

| Model                       | BK210  | BK310  |
|-----------------------------|--|--|
| Climate Class               | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 390  | 590  |
| Net Volume, l               | 380  | 585  |
| External Dimensions, WxDxH  | 1510x800x850   | 2020x800x850   |
| Internal Dimensions, WxDxH  | 1020x520x589   | 1520x520x589   |
| Doors                       | 2 solid  | 3 solid  |
| Shelves/Baskets             | 2, 400x600   | 3, 400x600   |
| Outer Body                  | SS304  | SS304  |
| Interior                    | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      |
| Lock                        | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 140  | 152  |
| Net Weight, kg              | 130  | 137  |
| Noise Level, dB(A)          | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  |
| Thermometer                 | Y  | Y  |
| Refrigerant                 | R134a  | R134a  |
| Charge, g                   | 230  | 250  |
| Internal Light              | N  | N  |

## » Undercounters GN1/1



UC5210

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Adjustable legs
- Digital temperature display



UC5360

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 6 drawers
- Adjustable legs
- Digital temperature display

### Technical specifications

| Model                       | UC5210             | UC5240             | UC5310             | UC5360             | UC5410             | UC5480             |
|-----------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Climate Class               | ST                 | ST                 | ST                 | ST                 | ST                 | ST                 |
| Temperature Range, °C       | -2 - 8             | -2 - 8             | -2 - 8             | -2 - 8             | -2 - 8             | -2 - 8             |
| Gross Volume, l             | 180                | 180                | 277                | 277                | 310                | 310                |
| Net Volume, l               | 170                | 170                | 262                | 262                | 300                | 300                |
| External Dimensions, WxDxH  | 1360x700x650       | 1360x700x650       | 1795x700x650       | 1795x700x650       | 2230x700x650       | 2230x700x650       |
| Internal Dimensions, WxDxH  | -                  | -                  | -                  | -                  | -                  | -                  |
| Doors                       | 2 hinged           | 4 drawers          | 3 hinged           | 6 drawers          | 4 hinged           | 8 drawers          |
| Shelves/Baskets             | 2, GN1/1           | 0                  | 3, GN1/1           | 0                  | 4, GN1/1           | 0                  |
| Outer Body                  | SS304              | SS304              | SS304              | SS304              | SS304              | SS304              |
| Interior                    | SS304              | SS304              | SS304              | SS304              | SS304              | SS304              |
| Castors/Foot                | 4 adjustable legs  | 4 adjustable legs  | 4 adjustable legs  | 4 adjustable legs  | 6 adjustable legs  | 6 adjustable legs  |
| Lock                        | N                  | N                  | N                  | N                  | N                  | N                  |
| Voltage/Frequency, V/Hz     | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         |
| Input Power, W              | 350                | 350                | 350                | 350                | 350                | 350                |
| Energy Consumption, kWh/24h | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk |
| Gross Weight, kg            | 95                 | 115                | 122                | 152                | 150                | 190                |
| Net Weight, kg              | 82                 | 102                | 106                | 136                | 130                | 170                |
| Noise Level, dB(A)          | 42                 | 42                 | 42                 | 42                 | 42                 | 42                 |
| Type of Cooling             | Fan assisted       | Fan assisted       | Fan assisted       | Fan assisted       | Fan assisted       | Fan assisted       |
| Type of Defrost             | Automatic          | Automatic          | Automatic          | Automatic          | Automatic          | Automatic          |
| Controller                  | Digital            | Digital            | Digital            | Digital            | Digital            | Digital            |
| Thermometer                 | Y                  | Y                  | Y                  | Y                  | Y                  | Y                  |
| Refrigerant                 | R134a              | R134a              | R134a              | R134a              | R134a              | R134a              |
| Charge, g                   | 230                | 230                | 230                | 230                | 250                | 250                |
| Internal Light              | N                  | N                  | N                  | N                  | N                  | N                  |



GN1/1 shelves



GN1/1 drawers



## » Saladette Counters GN1/1



SA912

- Gastronom 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 1 doors
- 1 GN1/1 shelves
- 2 Drawers
- Adjustable feet
- Digital temperature display



SA910

- Gastronom 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



SA914

- Gastronom 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 4 Drawers
- Adjustable feet
- Digital temperature display

### Technical specifications

| Model                       | SA910  | SA910BT  | SA912  | SA914  |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 10 to -20  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 230  | 230  | 230  | 230  |
| Net Volume, l               | 200  | 200  | 200  | 200  |
| External Dimensions, WxDxH  | 900x700x850  | 943x700x880  | 900x700x850  | 900x700x850  |
| Internal Dimensions, WxDxH  | 820x550x600  | 820x550x600  | 820x550x600  | 820x550x600  |
| Doors                       | 2  | 2  | 1, 2 drawers   | 4 drawers  |
| Shelves/Baskets             | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 0  |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      |
| Lock                        | N  | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 230  | 230  | 230  | 230  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 82   | 96   | 91   | 99   |
| Net Weight, kg              | 72   | 86   | 81   | 89   |
| Noise Level, dB(A)          | 42   | 42   | 42   | 42   |
| Type of Cooling             | Fan assisted   | Fan assisted   | Fan assisted   | Fan assisted   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | 165  | 165  | 165  | 165  |
| Internal Light              | N  | N  | N  | N  |
| Option: Charged with R600a  | ☑  |  | ☑  | ☑  |



## » Saladette Counters GN1/1



SA920

- Gastronom 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



Glass top as option



SA1045

- Gastronom 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



SA1365

- Gastronom 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display

### Technical specifications

| Model                       | SA920  | SA1045   | SA1365   | SA1365SS   |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 260  | 270  | 400  | 400  |
| Net Volume, l               | 230  | 240  | 368  | 368  |
| External Dimensions, WxDxH  | 900x700x850  | 1045x700x850   | 1365x700x850   | 1365x700x850   |
| Internal Dimensions, WxDxH  | 820x550x500  | 975x550x500  | 1225x550x500   | 1225x550x500   |
| Doors                       | 2  | 2  | 3  | 3  |
| Shelves/Baskets             | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      |
| Lock                        | N  | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 260  | 260  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 81   | 91   | 122  | 125  |
| Net Weight, kg              | 70   | 80   | 107  | 108  |
| Noise Level, dB(A)          | 42   | 42   | 42   | 42   |
| Type of Cooling             | Fan assisted   | Fan assisted   | Fan assisted   | Fan assisted   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | 165  | 165  | 265  | 265  |
| Internal Light              | N  | N  | N  | N  |
| Option: Charged with R600a  |  |  |  |  |



## » Sandwich Counters GN1/1



- SS920**
- Gastronomy 1/1 cupboard
  - Refrigerated topping well GN1/6
  - Hinged lid for saladette well
  - 2 doors
  - 2 GN 1/1 shelves
  - Stainless steel 304 interior
  - Stainless steel 304 exterior
  - Fan assisted cooling
  - Automatic defrost
  - Adjustable feet
  - Digital temperature display



Set of 2 drawers as separate kit



SS1435-6D with 6 drawers as standard



- SS1435**
- Gastronomy 1/1 cupboard
  - Refrigerated topping well GN1/6
  - Hinged lid for saladette well
  - 3 doors
  - 3 GN 1/1 shelves
  - Stainless steel 304 interior
  - Stainless steel 304 exterior
  - Fan assisted cooling
  - Automatic defrost
  - Adjustable feet
  - Digital temperature display

### Technical specifications

| Model                       | SS920  | SS1435   | SS1435-6D  |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 228  | 348  | 348  |
| Net Volume, l               | 201  | 320  | 320  |
| External Dimensions, WxDxH  | 900x700x800  | 1365x700x800   | 1365x700x800   |
| Internal Dimensions, WxDxH  | 830x550x600  | 1295x550x600   | 1295x550x600   |
| Doors                       | 2  | 3  | 3  |
| Shelves/Baskets             | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 6, GN1/1 drawers                                       |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 220  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 94   | 140  | 140  |
| Net Weight, kg              | 72   | 120  | 120  |
| Noise Level, dB(A)          | 42   | 42   | 42   |
| Type of Cooling             | Fan assisted   | Fan assisted   | Fan assisted   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 185  | 265  | 265  |
| Internal Light              | N  | N  | N  |
| Option: Charged with R600a  |  |  |  |

## » Sandwich Counters



**SS7200**

- Gastronorm 1/1 cupboard
- Refrigerated topping well GN1/3
- Hinged lid for saladette well
- 2 doors
- 2 GN 1/1 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- Adjustable legs
- Digital temperature display

Set of 2 drawers as separate kit



**SS8300**

- Euronom cupboard
- Refrigerated topping well GN1/3
- Hinged lid for saladette well
- 3 doors
- 3, 400x600 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- Adjustable legs
- Digital temperature display

### Technical specifications

| Model                       | SS7200   | SS7300   | SS8200   | SS8300   |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 330  | 439  | 362  | 530  |
| Net Volume, l               | 297  | 407  | 337  | 497  |
| External Dimensions, WxDxH  | 1300x700x1050  | 1785x700x1050  | 1910x600x1050  | 2020x600x1050  |
| Internal Dimensions, WxDxH  | 920x520x630  | 1237x520x630   | 1020x430x630   | 1520x430x630   |
| Doors                       | 2 self closing   | 3 self closing   | 2 self closing   | 3 self closing   |
| Shelves/Baskets             | 1 coated each door                                       | 1 coated each door                                       | 1 coated each door                                       | 1 coated each door                                       |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs  | 4 adjustable legs  | 4 adjustable legs  | 4 adjustable legs  |
| Lock                        | N  | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 230-240/50   | 230-240/50   | 230-240/50   | 230-240/50   |
| Input Power, W              | 260  | 260  | 260  | 260  |
| Energy Consumption, kWh/24h | See <a href="http://www.liebfeld.dk">www.liebfeld.dk</a> | See <a href="http://www.liebfeld.dk">www.liebfeld.dk</a> | See <a href="http://www.liebfeld.dk">www.liebfeld.dk</a> | See <a href="http://www.liebfeld.dk">www.liebfeld.dk</a> |
| Gross Weight, kg            | 145  | 180  | 180  | 192  |
| Net Weight, kg              | 125  | 155  | 140  | 164  |
| Noise Level dB(A)           | 42   | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | 230  | 230  | 230  | 250  |
| Internal Light              | N  | N  | N  | N  |



## » Pizza Counters GN1/1



**PT920**

- Granite table top
- Suitable for GN pans (not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**PT930**

- Granite table top
- Suitable for GN pans (not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**PT1365**

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display
- Topping unit designed for GN pans

### Technical specifications

| Model                       | PT920  | PT930  | PT1365   |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 250  | 400  | 400  |
| Net Volume, l               | 230  | 368  | 368  |
| External Dimensions, WxDxH  | 900x700x1100   | 1365x700x1100  | 1400x700x1415  |
| Internal Dimensions, WxDxH  | 820x550x800  | 1285x550x800   | 1255x550x800   |
| Doors                       | 2  | 3  | 3  |
| Shelves/Baskets             | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     | 1 each door, GN1/1                                     |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable feet                                      | 4 adjustable feet                                      | 4 adjustable feet                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 220  | 220  | 220  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 192  | 175  | 165  |
| Net Weight, kg              | 90   | 155  | 148  |
| Noise Level, dB(A)          | 42   | 42   | 42   |
| Type of Cooling             | Fan assisted   | Fan assisted   | Fan assisted   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 165  | 265  | 265  |
| Internal Light              | N  | N  | N  |
| Option: Charged with R600a  |  |  |  |

## » Pizza Counters



**PT1200**

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 doors
- Guides for 7 Pizza trays each door 400x600
- Adjustable legs
- Digital temperature display
- Topping unit designed for GN pans



Sides for pizza trays



7 ambient dough drawers on PT1310



**PT1300**

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 doors
- Guides for 7 Pizza trays each door
- Adjustable legs
- Digital temperature display
- Topping unit designed for GN pans

### Technical specifications

| Model                       | PT1200   | PT1300   | PT1310   |
|-----------------------------|--|--|--|
| Climate Class               | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 10  | 2 to 10  | 2 to 10  |
| Gross Volume, l             | 390  | 590  | 390  |
| Net Volume, l               | 370  | 565  | 370  |
| External Dimensions, WxDxH  | 1510x800x1415  | 2045x800x1415  | 2045x800x1415  |
| Internal Dimensions, WxDxH  | 1652x820x949   | 1652x820x949   | 1652x820x949   |
| Doors                       | 2 self closing   | 3 self closing   | 2 self closing, 7 drawers                              |
| Shelves/Baskets             | Guides for 7 Pizza trays each door                     | Guides for 7 Pizza trays each door                     | Guides for 7 Pizza trays each door                     |
| Outer Body                  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  |
| Castors/Feet                | 4 adjustable legs                                      | 4 adjustable legs                                      | 4 adjustable legs                                      |
| Lock                        | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 260  | 260  | 260  |
| Energy Consumption, kWh/24h | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> | See <a href="http://www.tefcold.dk">www.tefcold.dk</a> |
| Gross Weight, kg            | 275  | 340  | 380  |
| Net Weight, kg              | 258  | 320  | 363  |
| Noise Level dB(A)           | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost             | Automatic  | Automatic  | Automatic  |
| Controller                  | Digital  | Digital  | Digital  |
| Thermometer                 | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  |
| Charge, g                   | 230  | 250  | 230  |
| Internal Light              | N  | N  | N  |



# » Refrigerated Topping Unit



**VK38-200**

- Accepts GN1/3 pans (Not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Static cooling
- Glass structure for protection of food
- Adjustable feet
- Digital temperature display



Glass structure for protection of food



Stainless steel lid as option



Suited for Gastronom pans



Digital thermometer with clear blue display

### Technical specifications

| Model                       | VK33-120           | VK33-140           | VK33-150           | VK33-160           | VK33-180           | VK33-200           |
|-----------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Climate Class               | ST                 | ST                 | ST                 | ST                 | ST                 | ST                 |
| Temperature Range, °C       | 2 to 10            | 2 to 10            | 2 to 10            | 2 to 10            | 2 to 10            | 2 to 10            |
| Gross Volume, l             | 32                 | 42                 | 44                 | 48                 | 55                 | 63                 |
| Net Volume, l               | 32                 | 40                 | 44                 | 48                 | 55                 | 62                 |
| Pans                        | -                  | -                  | -                  | -                  | -                  | -                  |
| External Dimensions, WxDxH  | 1200x335x225       | 1400x335x225       | 1500x335x225       | 1600x335x225       | 1800x335x225       | 2000x335x225       |
| Internal Dimensions, WxDxH  | 845x265x155        | 1045x265x155       | 1145x265x155       | 1245x265x155       | 1445x265x155       | 1645x265x155       |
| Doors                       | 0                  | 0                  | 0                  | 0                  | 0                  | 0                  |
| Shelves/Baskets             | 5, GN1/4 opt.      | 6, GN1/4 opt.      | 7, GN1/4 opt.      | 7, GN1/4 opt.      | 8, GN1/4 opt.      | 10, GN1/4 opt.     |
| Outer Body                  | SS304              | SS304              | SS304              | SS304              | SS304              | SS304              |
| Interior                    | SS304              | SS304              | SS304              | SS304              | SS304              | SS304              |
| Castors/Foot                | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  |
| Lock                        | N                  | N                  | N                  | N                  | N                  | N                  |
| Voltage/Frequency, V/Hz     | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         |
| Input Power, W              | 340                | 340                | 340                | 340                | 340                | 340                |
| Energy Consumption, kWh/24h | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk |
| Gross Weight, kg            | 27                 | 29                 | 31                 | 32                 | 34                 | 38                 |
| Net Weight, kg              | 25                 | 27                 | 29                 | 30                 | 32                 | 34                 |
| Noise Level, dB(A)          | 47                 | 47                 | 47                 | 47                 | 47                 | 47                 |
| Type of Cooling             | Static             | Static             | Static             | Static             | Static             | Static             |
| Type of Defrost             | Manual             | Manual             | Manual             | Manual             | Manual             | Manual             |
| Controller                  | Electronic         | Electronic         | Electronic         | Electronic         | Electronic         | Electronic         |
| Thermometer                 | Y                  | Y                  | Y                  | Y                  | Y                  | Y                  |
| Refrigerant                 | R134a              | R134a              | R134a              | R134a              | R134a              | R134a              |
| Charge, g                   | 120                | 130                | 130                | 135                | 145                | 155                |
| Option: Charged with R600a  | 🌱                  | 🌱                  | 🌱                  | 🌱                  | 🌱                  | 🌱                  |

### Technical specifications

| Model                       | VK38-120           | VK38-150           | VK38-160           | VK38-180           | VK38-200           |
|-----------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Climate Class               | ST                 | ST                 | ST                 | ST                 | ST                 |
| Temperature Range, °C       | 2 to 10            | 2 to 10            | 2 to 10            | 2 to 10            | 2 to 10            |
| Gross Volume, l             | 40                 | 54                 | 59                 | 69                 | 76                 |
| Net Volume, l               | 40                 | 54                 | 59                 | 69                 | 76                 |
| Pans                        | -                  | -                  | -                  | -                  | -                  |
| External Dimensions, WxDxH  | 1200x395x225       | 1500x395x225       | 1600x395x225       | 1800x395x225       | 2000x395x225       |
| Internal Dimensions, WxDxH  | 845x305x155        | 1145x305x155       | 1245x305x155       | 1445x305x155       | 1645x305x155       |
| Doors                       | 0                  | 0                  | 0                  | 0                  | 0                  |
| Shelves/Baskets             | 4, GN1/3 opt.      | 6, GN1/3 opt.      | 7, GN1/3 opt.      | 8, GN1/3 opt.      | 5, GN1/3 opt.      |
| Outer Body                  | SS304              | SS304              | SS304              | SS304              | SS304              |
| Interior                    | SS304              | SS304              | SS304              | SS304              | SS304              |
| Castors/Foot                | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  | 4 adjustable feet  |
| Lock                        | N                  | N                  | N                  | N                  | N                  |
| Voltage/Frequency, V/Hz     | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         | 220-240/50         |
| Input Power, W              | 340                | 340                | 340                | 340                | 340                |
| Energy Consumption, kWh/24h | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk | See www.tefcold.dk |
| Gross Weight, kg            | 30                 | 33                 | 34                 | 38                 | 38                 |
| Net Weight, kg              | 28                 | 31                 | 32                 | 34                 | 36                 |
| Noise Level, dB(A)          | 47                 | 47                 | 47                 | 47                 | 47                 |
| Type of Cooling             | Static             | Static             | Static             | Static             | Static             |
| Type of Defrost             | Manual             | Manual             | Manual             | Manual             | Manual             |
| Controller                  | Electronic         | Electronic         | Electronic         | Electronic         | Electronic         |
| Thermometer                 | Y                  | Y                  | Y                  | Y                  | Y                  |
| Refrigerant                 | R134a              | R134a              | R134a              | R134a              | R134a              |
| Charge, g                   | 120                | 130                | 135                | 145                | 155                |
| Option: Charged with R600a  | 🌱                  | 🌱                  | 🌱                  | 🌱                  | 🌱                  |

## » Cooling Wells GN1/1



**CW3**

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Static cooling
- Digital temperature display
- Suitable for built-in

### Technical specifications

| Model                       | CW2  | CW3  | CW4  | CW5  |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 8   | 2 to 8   | 2 to 8   | 2 to 8   |
| Gross Volume, l             | 69   | 104  | 159  | 170  |
| Net Volume, l               | 69   | 102  | 156  | 166  |
| Pans                        | -  | -  | -  | -  |
| External Dimensions, WxDxH  | 788x688x538  | 1102x688x538   | 1436x688x538   | 1770x688x538   |
| Built-in Dimensions, WxD    | 748x650  | 1075x650   | 1405x650   | 1740x650   |
| Doors                       | N  | N  | N  | N  |
| Shelves/Baskets             | 2 x GN1/1 option                                     | 3 x GN1/1 option                                     | 4 x GN1/1 option                                     | 5 x GN1/1 option                                     |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Foot                | N  | N  | N  | N  |
| Lock                        | N  | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 250  | 250  | 250  | 250  |
| Energy Consumption, kWh/24h | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> |
| Gross Weight, kg            | 42   | 47   | 52   | 58   |
| Net Weight, kg              | 34   | 38   | 42   | 46   |
| Noise Level, dB(A)          | 42   | 42   | 42   | 42   |
| Type of Cooling             | Static   | Static   | Static   | Static   |
| Type of Defrost Controller  | Automatic  | Automatic  | Automatic  | Automatic  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | -  | -  | -  | -  |



Static cooling



Ventilated cooling

### Technical specifications

| Model                       | CW2/V  | CW3/V  | CW4/V  | CW5/V  |
|-----------------------------|--|--|--|--|
| Climate Class               | ST   | ST   | ST   | ST   |
| Temperature Range, °C       | 2 to 8   | 2 to 8   | 2 to 8   | 2 to 8   |
| Gross Volume, l             | 111  | 166  | 221  | 227  |
| Net Volume, l               | 110  | 164  | 218  | 223  |
| Pans                        | -  | -  | -  | -  |
| External Dimensions, WxDxH  | 788x688x638  | 1122x688x638   | 1456x688x638   | 1790x688x638   |
| Built-in Dimensions, WxD    | 756x655  | 1090x655   | 1424x655   | 1758x655   |
| Doors                       | N  | N  | N  | N  |
| Shelves/Baskets             | 2 x GN1/1 option                                     | 3 x GN1/1 option                                     | 4 x GN1/1 option                                     | 5 x GN1/1 option                                     |
| Outer Body                  | SS304  | SS304  | SS304  | SS304  |
| Interior                    | SS304  | SS304  | SS304  | SS304  |
| Castors/Foot                | N  | N  | N  | N  |
| Lock                        | N  | N  | N  | N  |
| Voltage/Frequency, V/Hz     | 220-240/50   | 220-240/50   | 220-240/50   | 220-240/50   |
| Input Power, W              | 260  | 260  | 260  | 260  |
| Energy Consumption, kWh/24h | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> | See <a href="http://www.tfcold.dk">www.tfcold.dk</a> |
| Gross Weight, kg            | 46   | 52   | 58   | 64   |
| Net Weight, kg              | 38   | 42   | 46   | 50   |
| Noise Level, dB(A)          | 42   | 42   | 42   | 42   |
| Type of Cooling             | Ventilated   | Ventilated   | Ventilated   | Ventilated   |
| Type of Defrost Controller  | Automatic  | Automatic  | Automatic  | Automatic  |
| Thermometer                 | Y  | Y  | Y  | Y  |
| Refrigerant                 | R134a  | R134a  | R134a  | R134a  |
| Charge, g                   | -  | -  | -  | -  |

# » Blast freezer / Chiller GN1/1



**BLC14**

- Stainless steel exterior
- Case sensor included
- Programmable thermostat
- 4 pre-set programs
- Guides for GN1/1 or 400x600 trays
- Self closing door
- Replaceable gasket
- Automatic defrost, hot gas
- Adjustable legs



Option: Thermal printer



**BLC3**

- Stainless steel exterior
- Case sensor included
- Programmable thermostat
- 4 pre-set programs
- Guides for GN1/1 or 400x600 trays
- Self closing door
- Replaceable gasket
- Automatic defrost, hot gas
- Adjustable legs



**BLC10**

- Stainless steel exterior
- Case sensor included
- Programmable thermostat
- 4 pre-set programs
- Guides for GN1/1 or 400x600 trays
- Self closing door
- Replaceable gasket
- Automatic defrost, hot gas
- Adjustable legs

## Technical specifications

| Model                                       | BLC3                    | BLC5                    | BLC10                   | BLC14                   |
|---|-------------------------|-------------------------|-------------------------|-------------------------|
| Climate Class                               | ST                      | ST                      | ST                      | ST                      |
| Temperature Range, °C                       | -18 to +70 / -13 to +70 | -18 to +70 / -13 to +70 | -18 to +70 / -13 to +70 | -18 to +70 / -13 to +70 |
| Gross Volume, l                             | 82                      | 111                     | 242                     | 319                     |
| Net Volume, l                               | 62                      | 100                     | 232                     | 299                     |
| Capacity, kg (+70 °C to +3 °C in 90 min.)   | 10                      | 16                      | 36                      | 50                      |
| Capacity, kg (+70 °C to -18 °C in 240 min.) | 8                       | 12                      | 25                      | 35                      |
| External Dimensions, WxDxH                  | 800x420x230             | 800x420x230             | 800x420x230             | 800x420x230             |
| Internal Dimensions, WxDxH                  | 660x420x190             | 660x420x190             | 660x420x190             | 660x420x190             |
| Doors                                       | 1 self closing          | 1 self closing          | 1 self closing          | 1 self closing          |
| Guides for trays                            | 3, GN1/1 or EN400x600   | 5, GN1/1 or EN400x600   | 10, GN1/1 or EN400x600  | 14, GN1/1 or EN400x600  |
| Outer Body                                  | SS304                   | SS304                   | SS304                   | SS304                   |
| Interior                                    | SS304                   | SS304                   | SS304                   | SS304                   |
| Castors/Feet                                | 4 adjustable legs       | 4 adjustable legs       | 4 adjustable legs       | 4 adjustable legs       |
| Lock  | N                       | N                       | N                       | N                       |
| Voltage/Frequency, V/Hz                     | 220-240/50              | 220-240/50              | 220-240/50              | 380-400/50              |
| Input Power, W                              | 770                     | 800                     | 1298                    | 2000                    |
| Energy Consumption, kWh/24h                 | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      | See www.tefcold.dk      |
| Gross Weight, kg                            | 162                     | 125                     | 190                     | 266                     |
| Net Weight, kg                              | 80                      | 95                      | 150                     | 210                     |
| Noise Level, dB(A)                          | 49                      | 49                      | 49                      | 49                      |
| Type of Cooling                             | Blast                   | Blast                   | Blast                   | Blast                   |
| Type of Defrost                             | Automatic, hot gas      | Automatic, hot gas      | Automatic, hot gas      | Automatic, hot gas      |
| Controller                                  | Programmable            | Programmable            | Programmable            | Programmable            |
| Thermometer                                 | Y                       | Y                       | Y                       | Y                       |
| Refrigerant                                 | R404a                   | R404a                   | R404a                   | R404a                   |
| Charge, g                                   | 700                     | 800                     | 900                     | 900                     |
| Internal Light                              | N                       | N                       | N                       | N                       |