

TEFCOLD® 

# Gastroline

Stainless Steel Products

Counters | Cooling Wells | Pizza | Saladette | Sandwich | Upright | Vitrine



## About Tefcold

TEFCOLD was founded in 1987 by a group of people with years of experience in the domestic and commercial refrigeration industry. The objectives were to develop, manufacture and distribute refrigerators and freezers with high quality for the global markets.

In 2003 the product range was extended with products for the HoReCa market.

The majority of the Tefcold equipment is produced according to the customers' specifications. Standard equipment can be shipped directly from our warehouses to the customers' when urgently needed.

In close cooperation with our customers the TEFCOLD team takes active part in the developing process, production planning and quality control in order to meet your demands. TEFCOLD is reliable and experienced when it comes to branded cabinets for the beverage and ice cream industries, and we aim to be the supplier of choice in our line of business.

For several years environmental issues have had top priority. TEFCOLD is focusing on equipment providing optimum solutions in order to take active part in the reduction of the global energy consumption.

Thanks to a constantly growing number of loyal customers TEFCOLD has increased sales significantly over the past years.

The AAA ratings by Dun and Bradstreet make TEFCOLD a reliable supplier.



## Stainless Steel Products

The Tefcold Gastro Line range is produced with focus on high quality steel and easy maintenance and offers a wide diversity of options.

Both Gastronorm and Euronorm standard counters are available, and we are pleased to introduce our new line of Undercounters.

Pizza Tables produced in stainless steel and granite are available in many different sizes, with or without drawers. Several models are delivered with refrigerated topping units.

The Saladette range is suitable for Gastronorm pans, and is available with or without hinged lid and saladette well. The Sandwich Table range accepts Gastronorm pans in the refrigerated topping section. Drawers are offered as option, and glass structures for protection/display of food can be supplied for some of the models.

The Upright range offers a variety of options for combining matching Refrigerators and Freezers. Cabinets for both Gastronorm and Euronorm trays are offered, as well as special cabinets for storage of ice cream or fish. Several products are available with glass doors or with double- or half-doors.

The Chilled Topping Units are offered in different sizes suitable for any purpose. Each model accepts Gastronorm pans and is delivered with either glass structure for better display and protection of toppings or with stainless steel lid.



# » Snack freezer / Chiller



Lock and digital thermometer



Bottom shelf available

## RF500 SNACK

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable shelves
- 4 castors, 2 with brake
- Static cooling
- Digital thermometer



#### RK500 SNACK

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable shelves
- 4 castors, 2 with brake
- Fan assisted cooling
- Automatic defrost
- Digital thermometer

### Technical specifications

Model	RF500 SNACK	RK500 SNACK
Climate Class	ST	ST
Temperature Range, °C	-10 to -20	-2 to 8
Gross Volume, l	450	450
Net Volume, l	429	429
External Dimensions, WxDxH	680x700x1900	680x700x1900
Internal Dimensions, WxDxH	560x553x1380	560x553x1380
Doors	1 self closing solid	1 self closing solid
Shelves/Baskets	3	3
Outer Body	SS304	SS304
Interior	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	600	300
Energy Consumption, kWh/24h	8	2,4
Gross Weight, kg	140	140
Net Weight, kg	130	130
Noise Level dbA	42	42
Type of Cooling	Static	Fan assisted
Type of Defrost	Manual	Automatic
Controller	Digital	Digital
Thermometer	Y	Y
Refrigerant	R404a	R134a
Charge, g	390	-
Internal Light	N	N
Canopy Light	N	N



## » Upright freezer / Chiller



### RK505

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable shelves
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer



#### RK1010

- Stainless steel exterior
- Lock fitted as standard
- 2 self-closing doors
- 6 Adjustable shelves
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer

### Technical specifications

Model	RF505	RF1010	RK505	RK1010
Climate Class, N,SN,ST,T	ST	ST	ST	ST
Temperature Range, °C	-18 to -24	-18 to -24	-2 to 8	-2 to 8
Gross Volume, l	466	976	466	976
Net Volume, l	429	900	429	900
External Dimensions, WxDxH	680x710x2010	1340x710x2010	680x710x2010	1340x710x2010
Internal Dimensions, WxDxH	560x553x1386	1220x553x1386	560x553x1386	1220x553x1386
Doors	1 solid SS304	2 solid SS304	1 solid SS304	2 solid SS304
Shelves/Baskets	3 coated steel	6 coated steel	3 coated steel	6 coated steel
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	600	1000	300	650
Energy Consumption, kWh/24h	8,0	9,0	2,4	5,4
Gross Weight, kg	145	195	145	195
Net Weight, kg	135	180	135	180
Noise Level dbA	45	45	45	45
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R404a	R404a	R134a	R134a
Charge, g	390	500	210	320
Internal Light	N	N	N	N
Canopy Light	N	N	N	N



# » Upright freezer / Chiller GN2/1



Kits for Euronorm available



Castor with brake

## RK710G

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing glass door
- 3 Adjustable GN2/1 shelves
- Interior light
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs





**RF710**

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 3 Adjustable GN2/1 shelves
- Interior light
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs



**RK1420**

- Stainless steel exterior
- Lock fitted as standard
- 2 self-closing doors
- 6 Adjustable GN2/1 shelves
- Suitable for fresh meat (-2/+2)
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs

## Technical specifications

Model	RF710	RF1420	RK710	RK1420	RK710G	RK1420G
Climate Class	ST	ST	ST	ST	ST	ST
Temperature Range, °C	-18 to -24	-18 to -24	-2 to 10	-2 to 10	2 to 10	2 to 10
Gross Volume, l	650	1410	650	1410	650	1410
Net Volume, l	597	1325	597	1325	597	1325
External Dimensions, WxDxH	740x850x2010	1480x850x2010	740x850x2010	1480x850x2010	740x850x2010	1480x850x2010
Internal Dimensions, WxDxH	624x685x1396	1360x685x1396	624x685x1396	1360x685x1396	624x685x1396	1360x685x1396
Doors	1 self closing solid	2 self closing solid	1 self closing solid	2 self closing solid	1 self closing glass	2 self closing glass
Shelves/Baskets	3, GN2/1	6, GN2/1	3, GN2/1	6, GN2/1	3, GN2/1	6, GN2/1
Outer Body	SS304	SS304	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304	SS304	SS304
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	1000	1000	456	650	456	650
Energy Consumption, kWh/24h	9	9,6	4,7	5,4	4,7	5,4
Gross Weight, kg	147	220	143	213	143	213
Net Weight, kg	138	198	134	198	134	198
Noise Level dbA	48	48	48	48	48	48
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R404a	R404a	R134a	R134a	R134a	R134a
Charge, g	460	500	300	500	300	500
Internal Light	25 W	2x25 W	25 W	2x25 W	25 W	2x25 W
Canopy Light	N	N	N	N	N	N



## » Upright freezer / Chiller



Stainless steel perforated risers

### RKS600 FISH

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 8 trays for fish
- 4 castors, 2 with brake
- Static cooling
- Manual defrost
- Digital thermometer
- Option: Adjustable legs



### BK850

- Stainless steel exterior
- Lock fitted as standard
- Reversible self-closing door
- 10 sets of slides for bakery trays included
- Interior light
- 4 castors, 2 with brake
- Ventilated cooling
- Automatic defrost
- Digital thermometer
- Option: Adjustable legs

## Technical specifications

Model	BF850	BK850	RKS600 FISH
Climate Class	ST	ST	ST
Temperature Range, °C	-18 to -24	-2 to 10	-6 to 8
Gross Volume, l	800	800	560
Net Volume, l	737	737	507
External Dimensions, WxDxH	740x990x2010	740x990x2010	680x810x2010
Internal Dimensions, WxDxH	624x846x1396	624x846x1396	-
Doors	1 self closing solid	1 self closing solid	1 self closing solid
Shelves/Baskets	10 guides	10 guides	8 trays
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	2 with, 2 without brake	2 with, 2 without brake	2 with, 2 without brake
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	1000	456	456
Energy Consumption, kWh/24h	9	4,7	4,7
Gross Weight, kg	152	149	145
Net Weight, kg	143	140	135
Noise Level dbA	48	48	48
Type of Cooling	Ventilated	Ventilated	Static
Type of Defrost	Automatic	Automatic	Manual
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R404a	R134a	R134a
Charge, g	440	350	-
Internal Light	25 W	25 W	N
Canopy Light	N	N	N



## » Upright freezer / Chiller GN2/1



### UR600S

- Stainless steel exterior
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves GN2/1
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs



#### UF600

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 7 Fixed shelves GN2/1
- Adjustable feet at front, rollers at back
- Static cooling
- Digital thermometer
- Option: Wheels or adjustable legs



#### UR600

- White cabinet
- White inner liner
- Lock fitted as standard
- Reversible door
- 4 Adjustable shelves GN2/1
- Adjustable feet at front, rollers at back
- Fan assisted cooling
- Automatic defrost
- Digital thermometer
- Option: Wheels or adjustable legs

## Technical specifications

Model	UF600	UF600S	UR600	UR600S
Climate Class	N	N	N	N
Temperature Range, °C	-10 to -24	-10 to -24	0 to 10	0 to 10
Gross Volume, l	600	600	600	600
Net Volume, l	555	555	570	570
External Dimensions, WxDxH	770x750x1900	770x750x1900	770x750x1900	770x750x1900
Internal Dimensions, WxDxH	-	-	-	-
Doors	1 solid White	1 solid SS430	1 solid White	1 solid SS430
Shelves/Baskets	7 fixed freezing, GN2/1	7 fixed freezing, GN2/1	3, GN2/1 and 1, 650x305	3, GN2/1 and 1, 650x305
Outer Body	White	SS430	White	SS430
Interior	ABS	ABS	ABS	ABS
Castors/Feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet	2 rollers and 2 feet
Lock	Y	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	350	350	200	200
Energy Consumption, kWh/24h	2,8	2,8	1,6	1,6
Gross Weight, kg	101	101	97	97
Net Weight, kg	94	94	90	90
Noise Level dbA	40	40	40	40
Type of Cooling	Static	Static	Fan assisted	Fan assisted
Type of Defrost	Manual	Manual	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	290	290	210	210
Internal Light	N	N	N	N
Canopy Light	N	N	N	N



# » Gastronorm Counters GN1/1



## CK7210

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Splashback fitted as standard
- Removeable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching freezer available



Available without splash back



Set of 2 drawers as separate kit



Set of 3 drawers as separate kit



### CK7410

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 4 self-closing doors
- Splashback fitted as standard
- Removeable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching freezer available

## Technical specifications

Model	CK7210	CK7310	CK7410
Climate Class	ST	ST	ST
Temperature Range, °C	-2 to 10	-2 to 10	-2 to 10
Gross Volume, l	282	417	553
Net Volume, l	272	402	533
External Dimensions, WxDxH	1360x700x950	1795x700x950	2230x700x950
Internal Dimensions, WxDxH	902x530x589	1337x530x589	1772x530x589
Doors	2 solid	3 solid	4 solid
Shelves/Baskets	2, GN1/1	3, GN1/1	4, GN1/1
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	6 adjustable legs
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	230	280
Energy Consumption, kWh/24h	2	2,6	3,4
Gross Weight, kg	108	149	173
Net Weight, kg	98	134	153
Noise Level dbA	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	230	230	250
Internal Light	N	N	N
Canopy Light	N	N	N



## » Gastronorm Counters GN1/1



### CK7210G

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing glass doors
- Internal LED light
- Removeable table top
- Adjustable legs
- Digital temperature display





### CK7310G

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing glass doors
- Internal LED light
- Removeable table top
- Adjustable legs
- Digital temperature display

## Technical specifications

Model	CK7210G	CK7310G	CK7410G
Climate Class	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	282	417	553
Net Volume, l	272	402	533
External Dimensions, WxDxH	1360x700x850	1795x700x850	2230x700x850
Internal Dimensions, WxDxH	902x530x589	1337x530x589	1772x530x589
Doors	2 glass	3 glass	4 glass
Shelves/Baskets	2, GN1/1	3, GN1/1	4, GN1/1
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	6 adjustable legs
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	230	280
Energy Consumption, kWh/24h	2,4	3	4
Gross Weight, kg	118	164	193
Net Weight, kg	108	149	173
Noise Level dbA	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	230	230	250
Internal Light	LED	LED	LED
Canopy Light	N	N	N



# » Gastronorm Counters GN1/1



## CF7210

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Splashback fitted as standard
- Removeable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits
- Matching chiller available



Castors as option



Digital thermometer with clear blue display



Available without splash back



### CF7310

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing doors
- Splashback fitted as standard
- Removeable table top
- Adjustable legs
- Digital temperature display
- Matching chiller available

## Technical specifications

Model	CF7210	CF7310	CF7410
Climate Class	ST	ST	ST
Temperature Range, °C	-10 to -20	-10 to -20	-10 to -20
Gross Volume, l	282	417	553
Net Volume, l	272	402	533
External Dimensions, WxDxH	1360x700x950	1795x700x950	2230x700x950
Internal Dimensions, WxDxH	902x530x589	1337x530x589	1772x530x589
Doors	2 solid	3 solid	4 solid
Shelves/Baskets	2, GN1/1	3, GN1/1	4, GN1/1
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	6 adjustable legs
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	700	700	700
Energy Consumption, kWh/24h	8,2	8,5	9
Gross Weight, kg	150	165	180
Net Weight, kg	140	150	160
Noise Level dbA	45	45	45
Type of Cooling	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R404a	R404a	R404a
Charge, g	300	300	300
Internal Light	N	N	N
Canopy Light	N	N	N



## » Snack Counters



### SK6210

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- 2 shelves
- Splashback as option
- Removeable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits



Set of 2 drawers as separate kit



Set of 3 drawers as separate kit



Castors as option



### SK6410

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 4 self-closing doors
- 4 shelves
- Splashback as option
- Removeable table top
- Adjustable legs
- Digital temperature display
- Drawers available as separate kits

## Technical specifications

Model	SK6210	SK6310	SK6410
Climate Class	ST	ST	ST
Temperature Range, °C	-2 to 10	-2 to 10	-2 to 10
Gross Volume, l	240	360	480
Net Volume, l	230	345	460
External Dimensions, WxDxH	1360x600x850	1795x600x850	2230x600x850
Internal Dimensions, WxDxH	902x430x589	1337x430x589	1772x430x589
Doors	1 solid, 2 drawers	2 solid, 3 drawers	4 solid
Shelves/Baskets	1, 328x430	2, 328x430	4, 328x430
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	6 adjustable legs
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	230	280
Energy Consumption, kWh/24h	2,2	2,6	3,2
Gross Weight, kg	98	135	143
Net Weight, kg	88	120	123
Noise Level dbA	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	230	230	250
Internal Light	N	N	N
Canopy Light	N	N	N



# » Euronorm Bakery Counters



## BK210

- Euronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- 2 shelves
- Removeable table top
- Adjustable legs
- Digital temperature display



Lock for compressor department



Set of 2 drawers as separate kit



Castors as option



### BK310

- Euronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 self-closing doors
- 3 shelves
- Removeable table top
- Adjustable legs
- Digital temperature display

## Technical specifications

Model	BK210	BK310
Climate Class	ST	ST
Temperature Range, °C	2 to 10	2 to 10
Gross Volume, l	390	580
Net Volume, l	380	565
External Dimensions, WxDxH	1510x800x850	2020x800x850
Internal Dimensions, WxDxH	1052x630x589	1562x630x589
Doors	2 solid	3 solid
Shelves/Baskets	2, 400x600	3, 400x600
Outer Body	SS304	SS304
Interior	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs
Lock	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	230	230
Energy Consumption, kWh/24h	2,4	2,6
Gross Weight, kg	140	152
Net Weight, kg	130	137
Noise Level dbA	42	42
Type of Cooling	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic
Controller	Digital	Digital
Thermometer	Y	Y
Refrigerant	R134a	R134a
Charge, g	230	250
Internal Light	N	N
Canopy Light	N	N



## » Undercounters GN1/1



### UC5210

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 self-closing doors
- Adjustable legs
- Digital temperature display



GN1/1 shelves



GN1/1 drawers





### UC5360

- 1/1 Gastronorm Cupboards
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 6 drawers
- Adjustable legs
- Digital temperature display

## Technical specifications

Model	UC5210	UC5240	UC5310	UC5360	UC5410	UC5480
Climate Class	ST	ST	ST	ST	ST	ST
Temperature Range, °C	-2 - 8	-2 - 8	-2 - 8	-2 - 8	-2 - 8	-2 - 8
Gross Volume, l	180	180	277	277	370	370
Net Volume, l	170	170	262	262	350	350
External Dimensions, WxDxH	1360x700x650	1360x700x650	1795x700x650	1795x700x650	2230x700x650	2230x700x650
Internal Dimensions, WxDxH	-	-	-	-	-	-
Doors	2 hinged	4 drawers	3 hinged	6 drawers	4 hinged	8 drawers
Shelves/Baskets	2, GN1/1	0	3, GN1/1	0	4, GN1/1	0
Outer Body	SS304	SS304	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	4 adjustable legs	4 adjustable legs	6 adjustable legs	6 adjustable legs
Lock	N	N	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	350	350	350	350	350	350
Energy Consumption, kWh/24h	1,8	1,8	2,2	2,2	2,4	2,4
Gross Weight, kg	95	115	122	152	150	190
Net Weight, kg	82	102	106	136	130	170
Noise Level dbA	42	42	42	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a
Charge, g	230	230	230	230	250	250
Internal Light	N	N	N	N	N	N



## » Saladette Counters GN1/1



### SA912

- Gastronorm 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 1 doors
- 1 GN1/1 shelves
- 2 Drawers
- Adjustable feet
- Digital temperature display



**SA910**

- Gastronorm 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**SA914**

- Gastronorm 1/1 cupboard
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 4 Drawers
- Adjustable feet
- Digital temperature display

## Technical specifications

Model	SA910	SA910BT	SA912	SA914
Climate Class	ST	ST	ST	ST
Temperature Range, °C	2 to 10	-10 to -20	2 to 10	2 to 10
Gross Volume, l	260	230	260	260
Net Volume, l	230	200	230	230
External Dimensions, WxDxH	900x700x850	943x700x860	900x700x850	900x700x850
Internal Dimensions, WxDxH	830x515x500	830x515x415	830x515x500	830x515x500
Doors	2	2	1, 2 drawers	4 drawers
Shelves/Baskets	1 each door, GN1/1	1 each door, GN1/1	1 each door, GN1/1	0
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	230	280	230	230
Energy Consumption, kWh/24h	2	4,5	2,1	2,1
Gross Weight, kg	82	96	91	99
Net Weight, kg	72	86	81	89
Noise Level dbA	42	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	165		165	165
Internal Light	N	N	N	N
Canopy Light	N	N	N	N



## » Saladette Counters GN1/1



### SA920

- Gastronorm 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



Glass top as option



**SA1045**

- Gastronorm 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**SA1365**

- Gastronorm 1/1 cupboard
- Hinged stainless cover for saladette well
- Polypropylene chopping board
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display

## Technical specifications

Model	SA920	SA1045	SA1365	SA1365SS
Climate Class	ST	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	260	270	400	400
Net Volume, l	230	240	368	368
External Dimensions, WxDxH	900x700x850	1045x700x850	1365x700x850	1365x700x850
Internal Dimensions, WxDxH	830x515x500	975x515x500	1295x515x500	1295x515x500
Doors	2	2	3	3
Shelves/Baskets	1 each door, GN1/1	1 each door, GN1/1	1 each door, GN1/1	1 each door, GN1/1
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	230	230	280	280
Energy Consumption, kWh/24h	2,4	2,5	2,7	2,6
Gross Weight, kg	81	91	122	125
Net Weight, kg	70	80	107	108
Noise Level dbA	42	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	165	165	265	265
Internal Light	N	N	N	N
Canopy Light	N	N	N	N



## » Sandwich Counters GN1/1



### SS920

- Gastronorm 1/1 cupboard
- Refrigerated topping well GN1/6
- Hinged lid for saladette well
- 2 doors
- 2 GN 1/1 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- Adjustable feet
- Digital temperature display



Set of 2 drawers as separate kit



### SS1435

- Gastronorm 1/1 cupboard
- Refrigerated topping well GN1/6
- Hinged lid for saladette well
- 3 doors
- 3 GN 1/1 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- Adjustable feet
- Digital temperature display

## Technical specifications

Model	SS920	SS1435
Climate Class	ST	ST
Temperature Range, °C	2 to 10	2 to 10
Gross Volume, l	228	348
Net Volume, l	201	320
External Dimensions, WxDxH	900x700x980	1365x700x980
Internal Dimensions, WxDxH	830x515x500	1295x515x500
Doors	2	3
Shelves/Baskets	1 each door, GN1/1	1 each door, GN1/1
Outer Body	SS304	SS304
Interior	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet
Lock	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	230	230
Energy Consumption, kWh/24h	2	2,4
Gross Weight, kg	94	140
Net Weight, kg	72	120
Noise Level dbA	42	42
Type of Cooling	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic
Controller	Digital	Digital
Thermometer	Y	Y
Refrigerant	R134a	R134a
Charge, g	165	265
Internal Light	N	N
Canopy Light	N	N



## » Sandwich Counters



### SS7200

- Gastronorm 1/1 cupboard
- Refrigerated topping well GN1/3
- Hinged lid for saladette well
- 2 doors
- 2 GN 1/1 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- Adjustable legs
- Digital temperature display



Set of 2 drawers as separate kit





### SS8300

- Euronorm cupboard
- Refrigerated topping well GN1/3
- Hinged lid for saladette well
- 3 doors
- 3, 400x600 shelves
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- Adjustable legs
- Digital temperature display

## Technical specifications

Model	SS7200	SS7300	SS8200	SS8300
Climate Class	ST	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	320	429	362	520
Net Volume, l	297	407	337	497
External Dimensions, WxDxH	1360x700x1050	1795x700x1050	1510x800x1050	2020x800x1050
Internal Dimensions, WxDxH	920x530x589	1337x530x589	1052x630x589	1562x630x589
Doors	2 self closing	3 self closing	2 self closing	3 self closing
Shelves/Baskets	1 coated each door	1 coated each door	1 coated each door	1 coated each door
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	4 adjustable legs	4 adjustable legs
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	280	280	280	340
Energy Consumption, kWh/24h	2,7	2,8	2,8	3,2
Gross Weight, kg	145	180	160	192
Net Weight, kg	125	155	140	164
Noise Level dbA	42	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	230	230	230	250
Internal Light	N	N	N	N
Canopy Light	N	N	N	N



## » Pizza Counters GN1/1



### PT920

- Granite table top
- Suitable for GN pans (not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 2 doors
- 2 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**PT930**

- Granite table top
- Suitable for GN pans (not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display



**PT1365**

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Fan assisted cooling
- Automatic defrost
- 3 doors
- 3 GN1/1 shelves
- Adjustable feet
- Digital temperature display
- Topping unit designed for GN pans

## Technical specifications

Model	PT920	PT930	PT1365
Climate Class	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	260	400	400
Net Volume, l	230	368	368
External Dimensions, WxDxH	900x700x1100	1365x700x1100	1400x700x1415
Internal Dimensions, WxDxH	830x515x500	1295x515x500	1295x515x500
Doors	2	3	3
Shelves/Baskets	1 each door, GN1/1	1 each door, GN1/1	1 each door, GN1/1
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	230	230	230
Energy Consumption, kWh/24h	2,2	2,4	2,4
Gross Weight, kg	102	175	165
Net Weight, kg	90	155	148
Noise Level dbA	42	42	42
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	165	265	265
Internal Light	N	N	N
Canopy Light	N	N	N



## » Pizza Counters



### PT1200

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 2 doors
- 7 Pizza trays each door 400x600
- Adjustable legs
- Digital temperature display
- Topping unit designed for GN pans



Slides for pizza trays



7 ambient dough drawers on PT1310



#### PT1300

- Granite table top
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Ventilated cooling
- Automatic defrost
- 3 doors
- 7 Pizza trays each door 400x600
- Adjustable legs
- Digital temperature display
- Topping unit designed for GN pans

## Technical specifications

Model	PT1200	PT1300	PT1310
Climate Class	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	390	580	390
Net Volume, l	370	565	370
External Dimensions, WxDxH	1510x800x1415	2045x800x1415	2045x800x1415
Internal Dimensions, WxDxH	1052x630x589	1562x630x589	1052x630x589
Doors	2 self closing	3 self closing	2 self closing, 7 drawers
Shelves/Baskets	1 each door, 400x600	1 each door, 400x600	1 each door, 400x600
Outer Body	SS304	SS304	SS304
Interior	SS304	SS304	SS304
Castors/Feet	4 adjustable legs	4 adjustable legs	4 adjustable legs
Lock	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	280	280	280
Energy Consumption, kWh/24h	2,4	2,8	2,4
Gross Weight, kg	275	340	380
Net Weight, kg	258	320	363
Noise Level dbA	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital
Thermometer	Y	Y	Y
Refrigerant	R134a	R134a	R134a
Charge, g	230	250	230
Internal Light	N	N	N
Canopy Light	N	N	N



# » Refrigerated Topping Unit



## VK38-200

- Accepts GN1/3 pans (Not supplied)
- Stainless steel 304 interior
- Stainless steel 304 exterior
- Static cooling
- Glass structure for protection of food
- Adjustable feet
- Digital temperature display

## Technical specifications

Model	VK33-120	VK33-140	VK33-150	VK33-160	VK33-180	VK33-200
Climate Class	ST	ST	ST	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	32	42	44	48	55	63
Net Volume, l	32	40	44	48	55	63
Pans	-	-	-	-	-	-
External Dimensions, WxDxH	1200x335x225	1400x335x225	1500x335x225	1600x335x225	1800x335x225	2000x335x225
Internal Dimensions, WxDxH	845x245x155	1045x245x155	1145x245x155	1245x245x155	1445x245x155	1645x245x155
Doors	0	0	0	0	0	0
Shelves/Baskets	5, GN1/4 opt.	6, GN1/4 opt.	7, GN1/4 opt.	7, GN1/4 opt.	8, GN1/4 opt.	10, GN1/4 opt.
Outer Body	SS304	SS304	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N	N	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	340	340	340	340	340	340
Energy Consumption, kWh/24h	2,8	2,8	2,8	2,8	2,8	2,8
Gross Weight, kg	27	29	31	32	34	36
Net Weight, kg	25	27	29	30	32	34
Noise Level dbA	47	47	47	47	47	47
Type of Cooling	Static	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual	Manual
Controller	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Thermometer	Y	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a
Charge, g	120	130	130	135	145	155
Internal Light	N	N	N	N	N	N
Canopy Light	N	N	N	N	N	N



Glass structure for protection of food



Stainless steel lid as option



Suited for Gastronorm pans



Digital thermometer with clear blue display

## Technical specifications

Model	VK38-120	VK38-150	VK38-160	VK38-180	VK38-200
Climate Class	ST	ST	ST	ST	ST
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	40	54	59	69	78
Net Volume, l	40	54	59	69	78
Pans	-	-	-	-	-
External Dimensions, WxDxH	1200x395x225	1500x395x225	1600x395x225	1800x395x225	2000x395x225
Internal Dimensions, WxDxH	845x305x155	1145x305x155	1245x305x155	1445x305x155	1645x305x155
Doors	0	0	0	0	0
Shelves/Baskets	4, GN1/3 opt.	6, GN1/3 opt.	7, GN1/3 opt.	8, GN1/3 opt.	9, GN1/3 opt.
Outer Body	SS304	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304	SS304
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	N	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	340	340	340	340	340
Energy Consumption, kWh/24h	2,8	2,8	2,8	2,8	3
Gross Weight, kg	30	33	34	36	38
Net Weight, kg	28	31	32	34	36
Noise Level dbA	47	47	47	47	47
Type of Cooling	Static	Static	Static	Static	Static
Type of Defrost	Manual	Manual	Manual	Manual	Manual
Controller	Electronic	Electronic	Electronic	Electronic	Electronic
Thermometer	Y	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a	R134a
Charge, g	120	130	135	145	155
Internal Light	N	N	N	N	N
Canopy Light	N	N	N	N	N



# » Cooling Wells GN1/1



## CW3

- Stainless steel 304 interior
- Stainless steel 304 exterior
- Static cooling
- Digital temperature display
- Suitable for build-in

## Technical specifications

Model	CW2	CW3	CW4	CW5
Climate Class	ST	ST	ST	ST
Temperature Range, °C	2 to 8	2 to 8	2 to 8	2 to 8
Gross Volume, l	69	104	139	170
Net Volume, l	68	102	136	166
Pans	-	-	-	-
External Dimensions, WxDxH	768x678x536	1102x678x536	1436x678x536	1770x678x536
Build-in Dimensions, WxD	740x650	1075x650	1405x650	1740x650
Doors	N	N	N	N
Shelves/Baskets	2 x GN1/1 option	3 x GN1/1 option	4 x GN1/1 option	5 x GN1/1 option
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	N	N	N	N
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	250	250	250	250
Energy Consumption, kWh/24h	-	-	-	-
Gross Weight, kg	42	47	52	58
Net Weight, kg	34	38	42	46
Noise Level dbA	42	42	42	42
Type of Cooling	Static	Static	Static	Static
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	-	-	-	-
Internal Light	N	N	N	N
Canopy Light	N	N	N	N





Suitable for build-in



Static cooling



Ventilated cooling

## Technical specifications

Model	CW2/V	CW3/V	CW4/V	CW5/V
Climate Class	ST	ST	ST	ST
Temperature Range, °C	2 to 8	2 to 8	2 to 8	2 to 8
Gross Volume, l	111	166	221	277
Net Volume, l	110	164	218	273
Pans	-	-	-	-
External Dimensions, WxDxH	788x688x636	1122x688x636	1456x688x636	1790x688x636
Build-in Dimensions, WxD	755x655	1090x655	1425x655	1755x655
Doors	N	N	N	N
Shelves/Baskets	2 x GN1/1 option	3 x GN1/1 option	4 x GN1/1 option	5 x GN1/1 option
Outer Body	SS304	SS304	SS304	SS304
Interior	SS304	SS304	SS304	SS304
Castors/Feet	N	N	N	N
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	280	280	280	280
Energy Consumption, kWh/24h	-	-	-	-
Gross Weight, kg	46	52	58	64
Net Weight, kg	38	42	46	50
Noise Level dbA	42	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Digital	Digital	Digital	Digital
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	-	-	-	-
Internal Light	N	N	N	N
Canopy Light	N	N	N	N