## Main features and benefits



**Robust worktop** Reinforced top with a rounded front and back edge, sealed at the back to avoid accumulation of dirt.



**Condensing unit** Removable on slides for inspection and cleaning.



Slides and racks Removable AISI 304 stainless steel racks and slides, without the need tools.



Forced air refrigeration Forced air refrigeration creates a perfect uniform temperature in each compartment and drawer.



**Reinforced drawers** Each compartment can be customised with GN1/2 - 1/3 - 2/3, -2°C to  $+8^{\circ}\text{C}$  or  $-15^{\circ}\text{C}$  to  $-22^{\circ}\text{C}$ refrigerated drawers.



Replaceable gaskets with high performance sealing Triple chamber geometry with innovative D7 compound, which grants 35% higher insulation efficiency than traditional models.



**Reinforced base** The modular reinforced base allows installation on castors, feet, a fixed or mobile plinth.



**Doors** Reversible self-closing doors with 105° stop. Stainless steel handle, thickness 2 mm.

## Other characteristics

Exterior, external back and interior in AISI 304 stainless steel

Anti-corrosion painted evaporator

Soundproofed engine compartment, left or right Internal and external radiused corners easy to clean

Automatic evaporation of condensing water

Plug-In and Remote versions with open base -2°+8°C e -15°-22°C

CFC/HCFC FREE. insulation thickness: 60 mm

Hot gas defrosting (Plug-In), electric (Remote)

Cosmo wi-fi monitor system (optional) and MODBUS-RT connection Eco-friendly refrigerant R290 GWP=3

Designed to operate efficiently in climate class 5

Customised finish with RAL colours

		1 door	2 doors	3 doors	4 doors			
<u>=0</u>	Lock with key for drawer 1/2 + 1/2	•	•	•	•	F		Lock system The lock is placed on the
	Lock with key for drawer 1/3 + 1/3 + 1/3				•		9	bottom part of the drawer.  Closure takes place through the coupling to the lower drawer or to the bottom of the counter.
©,,,,,	Lock with key for drawer 1/3 + 2/3	•	•	•	•		9	
	Glass door for -2°+8°C versions, h 710 and 760, 1 door*	•	•	•	•			
	Adjustable height of feet 145/195 mm, 1 piece Cod: M021145020	•	•	•	•			
	4 Swivel and brake castors, h 128 mm** Cod: O44400002001			•	_			
	6 Swivel and brake castors, h 128 mm Cod: O44600002001	_	_	_	•			
	RAL customisable colouring				•			
	Brackets for GN pans for drawer Cod: L223488086				•			
1/2	GN1/2 container + lids kit for drawer, h 150 mm Cod: O34412015001				•			
1/3 1/3 1/3	GN1/3 container + lids kit for drawer, h 150 mm Cod: O34413015001				•			
	Bottles shelf, stainless steel coating for GN1/1 shelf Cod: O261325530		•	-	-			
	Stainless steel shelf GN1/1 Cod: O241325530	•	•	•	•			

<sup>\*</sup> Available on request for other heights.
\*\* Not available for 1 door remote versions.