

Main features and benefits



Robust worktop

Reinforced top with a rounded front and back edge, sealed at the back to avoid accumulation of dirt.



Condensing unit

Removable on slides for inspection and cleaning.



Slides and racks

Removable AISI 304 stainless steel racks and slides, without the need tools.



Forced air refrigeration

Forced air refrigeration creates a perfect uniform temperature in each compartment and drawer.



Reinforced drawers

Each compartment can be customised with GN1/2 - 1/3 - 2/3, -2°C to +8°C or -15°C to -22°C refrigerated drawers.



Replaceable gaskets with high performance sealing

Triple chamber geometry with innovative D7 compound, which grants 35% higher insulation efficiency than traditional models.



Reinforced base

The modular reinforced base allows installation on castors, feet, a fixed or mobile plinth.



Doors

Reversible self-closing doors with 105° stop. Stainless steel handle, thickness 2 mm.

Other characteristics

Exterior, external back and interior in AISI 304 stainless steel

Internal and external radiused corners easy to clean

CFC/HCFC FREE, insulation thickness: 60 mm

Eco-friendly refrigerant R290 GWP=3

Anti-corrosion painted evaporator

Automatic evaporation of condensing water

Hot gas defrosting (Plug-In), electric (Remote)

Designed to operate efficiently in climate class 5

Soundproofed engine compartment, left or right

Plug-In and Remote versions with open base -2°/+8°C e -15°/-22°C

Cosmo wi-fi monitor system (optional) and MODBUS-RT connection

Customised finish with RAL colours

		1 door	2 doors	3 doors	4 doors
	Plastic coated shelf GN1/1 Cod: Q221325530	■	■	■	■
	Pair of type C slides 505 mm for GN1/1 shelf Cod: O12115052001	■	■	■	■
	Plug-in water unit -2°+8°C	■	■	■	■
	Plug-in water unit -15°-22°C	■	■	■	■
	Stainless steel evaporator -2°+8°C	■	■	■	■
CO ₂	Predisposition for connection to CO ₂ remote control unit	■	■	■	■
	R134a valve for remote -2°+8°C versions Cod: F310120020	■	■	■	■
	Serial interface, RS485 cable Cod: E020530010	■	■	■	■
	IP44 schuko socket with cover for plug-in version Cod: E74300003001	■	■	■	■
60 Hz	Special voltage 220V 60Hz	■	■	■	■
	Other special voltage	■	■	■	■
	Cosmo connection kit for 1 thermostat*** Cod: O92050002001	■	■	■	■

*** A Cosmo HUB (MODI, LEVTRONIC, VISION) is required for remote monitoring of Master counters.

■ available
— not available