



## Main features and benefits



### GN1/3 or GN 1/6 containers

Specific models are available with refrigerated spaces for GN1/3 or GN1/6 containers.



### Worktops available in stainless steel or granite

The solid and sturdy worktop is made of stainless steel AISI 304 or granite (optional).



### Counters with 2 depths

Models available with depths 700 mm (GN1/1 trays) or 800 mm (EN60x40 trays).



### Slides and racks

Removable AISI 304 stainless steel racks and slides, without the need tools.



### Condensing unit

Removable on slides for inspection and cleaning.



### Replaceable gaskets with high performance sealing

Triple chamber geometry with innovative D7 compound, which grants 35% higher insulation efficiency than traditional models.



### Reinforced base

The modular reinforced base allows installation on castors, feet, a fixed or mobile plinth.



### Doors

Reversible self-closing doors with 105° stop.

## Other characteristics

Exterior and interior in AISI 304 stainless steel. Internal and external radiused corners easy to clean

Anti-corrosion painted evaporator

Plug-In and Remote versions. Soundproofed engine compartment, left or right

Electric socket (optional)

Automatic evaporation of condensing water

MODBUS-RT connection











CFC/HCFC FREE, insulation thickness: 60 mm

Hot gas defrosting (Plug-In), electric (Remote)

Cosmo wi-fi monitor system (optional)

Eco-friendly refrigerant R290 GWP=3

Designed to operate efficiently in climate class 5

		2 doors	3 doors	4 doors
	Plastic coated shelf EN60x40 Cod: O222400600	■	■	■
	Pair of type L slides 605 mm for EN60x40 shelf Cod: O121260520	■	■	■
	Plug-in water unit extra cost	■	■	■
	Predisposition for connection to CO <sub>2</sub> remote control unit	■	■	■
	R134a valve for remote -2°+8°C versions Cod: F310120020	■	■	■
	Serial interface, RS485 cable Cod: E020530010	■	■	■
	IP44 schuko socket with cover for plug-in version Cod: E74300003001	■	■	■
	Special voltage 220V 60Hz	■	■	■
	Other special voltage	■	■	■
	Cosmo connection kit for 1 thermostat** Cod: O92050002001	■	■	■

\*\* A Cosmo HUB (MODI, LEVTRONIC, VISION) is required for remote monitoring of Prep-Station counters.

■ available  
— not available