## Main features and benefits




**Modular base**Allows installation on wheels, feet, fixed or mobile base.



Electronic expansion valve Regulates the quantity of the refrigerant fluid injected, improving performance by 25% and reducing consumption.



Replaceable gaskets with high performance insulation Triple chamber geometry with innovative D7 compound, which grants 35% higher insulation efficiency than traditional models.



Air flow circulation conveyor
The innovative air circulation system envelops the food while reducing the time of the cooling cycle.



Easy maintenance
The quick release system
for the front panel allows
the condenser battery to be
cleaned quickly, ensuring that
its performance over time
remains constant.



Ventilation panel opening
The evaporator is easy to
inspect. Its quick release
system makes cleaning and
maintenance easy.



**Slides and racks**Racks with positioning holes allow easy repositioning of the slides for EN60x40 and GN1/1 (excluded models L 710 mm).



Core probe
Developed with an exclusive ergonomic design, it can be easily dismantled and replaced thanks to a simple connector.
Multipoint or heated optional.

## Other characteristics

External and internal body is made of steel AISI 304

Hot gas defrosting (Plug-In), forced air (Remote)

Designed to operate efficiently in climate class 5

CFC/HCFC FREE, insulation thickness: 60 mm

Variable air flow condenser

MODBUS-RT connection

Touch screen 4.3" with USB socket

Anti-corrosion painted evaporator

Cosmo wi-fi supervision system Removable stainless steel racks without the need for tools

Door frame with anti-condensation system

Plug-In and Remote versions

		3T	5T GN	5T	6T GN	6T	7T GN	7T counter	7T	10T	14T	20TP 60x80	20T	20K
	Lowered foot h 55/70 mm, 1 piece Cod: M021055020	Ι	•	•	•	•	•	•	•	•	•	•	_	_
	4 Swivel and brake castors, h 128 mm Cod: O44400006001	1			•		•	•	•	•		•	•	_
	RAL customisable colouring				•		•	•		•		•	•	•
	Stainless steel shelf GN1/1 Cod: O241325530	-	•		•	•	•	•		•		-	•	_
	Plastic coated shelf GN1/1 Cod: O221325530	1	•	•	•	•	•	•		•		-	•	_
	Stainless steel shelf EN60x40 Cod: O241600400	-	_	•	_	•	_	•	•	-	•	•	-	_
	Plastic coated shelf EN60x40 Cod: O222400600	-	_	•	_	•	_	•	•	•		•	•	_
	Pair of type L slides 398 mm for GN-EN shelf Cod: O12124022001	-	_	•	_	•	_	•		-		_	-	_
	Stainless steel shelf GN2/1 Cod: O241650530	_	_	_	_	_	_	_	_	_	_	-	_	_
	Plastic coated shelf GN2/1 Cod: O221650530	-	_	-	-	_	_	-	-	_	_	•	-	_
	Pair of type L slides 755 mm for GN2/1-EN60x80 shelf Cod: O12127554001	-	_	_	_	_	_	_	-	_	_	-	_	_
<u></u>	Core probe with 3 reading points extra cost	_			•			•				•	•	•
*	Heated core probe with 1 reading point extra cost	Ι			•		•	•	•	•	•	•	•	•

availablenot available