

# Technical info

Model	Glasswashers		Front loaders			Hood type units			
	LB215M	LB275M	LF321M	LF322M	LF700M	LC411M	LC700M	LC900M	LC1200M
	LB215MA	LB275MA	LF321MA	LF322MA	LF700MA				
width (mm)	460	460	600	600	600	632	625	625	625
depth (mm)	520	520	600	600	600	765	760	760	760
height (mm)	635	695	820	820	1260	1460	1460	1460	1460
rack (mm)	400x400	400x400	500x500	500x500	500x500	500x500	500x500	500x500	500x500
washing cycle (sec.)	120	120	120/180	100/150	90/120	120/180	90/120/ 180/480	75/120/ 180/480	55/85/ 120/480
theoretical output* racks/h	30	30	30/20	36/24	40/30	40/30	40/30/20	48/30/20	65/42/30
clearance (mm)	215	275	360**	345**	345**	440	440	440	440
electrical supply	230V 50Hz		230V 50Hz	Multipower	Multipower	Multipower		400V 3N 50Hz	
wash pump (kW)	0,37	0,37	0,45	0,45	0,75	0,75	0,75	1,1	1,5
tank capacity (L)	13	13	21	21	21	22	42	42	42
tank heater (kW)	2	2	2	2	2	2	2	3	3
rinse water consumption (L)	2	2	3,5	3,5	3,5	3,2	3,5	3,5	3,5
booster capacity (L)	6	6	8,2	8,2	8,2	8,2	8,2	8,2	8,2
booster heater (kW)	2,5	2,5	3	5 - 2,5	6 - 3	7	6	8	9
total power (kW)	2,8	2,8	3,45	5,45	6,75	7,75	6,75	9,1	10,5
door switch	yes	yes	yes	yes	yes	yes	yes	yes	yes
built-in water softener	no / yes	no / yes	no / yes	no / yes	no / yes	no	no	no	no
weight (kg)	33 / 37	37 / 41	58 / 62	58 / 62	65 / 69	130	130	135	140
wash arms	PP	PP	PP	sst	sst	sst	sst	sst	sst
drain height (mm)	41	41	55	55	525	560	290	290	290
rinse aid dispenser	yes	yes	yes	yes	yes	yes	yes	yes	yes
detergent dispenser	option	option	option	option	option	option	option	option	option
drain pump	option	option	option	option	option	option	option	option	option
RCD	option	option	option	option	option	option	option	option	option

We reserve the right to modify technical features and pictures.

\* In the case of non-stop washing, the cycle duration might be automatically increased to ensure proper rinse temperature.

\*\* clearance for 530x375 trays with special rack.