

Technical

Data sheet



B116-B416 • 16-Comp Rack with Extenders

Dimensions: 500 x 500 x 105 mm

B116, 1 Extender:

Inside height to the frame: 70 mm

Compartment: 110 x 110 mm, weight: 1700gr

B216, 2 Extenders:

Inside height to the frame: 118 mm

Compartment: 110 x 110 mm, weight: 2200gr

B316, 3 Extenders:

Inside height to the frame: 168 mm

Compartment: 110 x 110 mm, weight: 2700gr

B416, 4 Extenders:

Inside height to the frame: 216 mm

Compartment: 110 x 110 mm, weight: 3200gr

Raw material

Raw material options:

PP

Master batch colour:

blue/red

Approvals:

All plastic polymers and master batch are free from Bisphenol A, PVC, antimicrobial additives and are approved for food contact packaging by FDA and meet the demands of the EU directive No 10/2011.



Packaging

B116: Box: CWK-25 (784 x 504 x 504 mm) à 1,190 kg = 1 x 8 pcs

B216: Box: CWK-25 (784 x 504 x 504 mm) à 1,190 kg = 1 x 5 pcs

B316: Box: CWK-25 (784 x 504 x 504 mm) à 1,190 kg = 1 x 4 pcs

B416: Box: CWK-25 (784 x 504 x 504 mm) à 1,190 kg = 1 x 3 pcs

B116: On pallet (EUR) 1200 x 800 x 15: 8 x 8 = 64 pcs

B216: On pallet (EUR) 1200 x 800 x 15: 8 x 5 = 40 pcs

B316: On pallet (EUR) 1200 x 800 x 15: 8 x 4 = 32 pcs

B416: On pallet (EUR) 1200 x 800 x 15: 8 x 3 = 24 pcs

Height incl. pallet: 2190 mm

Performance

Hot temperatures:

The resin material for the Rack with 16-Comp. Extenders resists temperatures up to +120°C. The product is dishwasher safe.

Cold temperatures:

The resin material for the the Rack with 16-Comp. Extenders resists temperatures down to -10°C. The product may be brittle at temperatures below 0°C.

Quality information:

Deviations in the product specifications in this data sheet of 0,05% or less on a rolling 12 months basis are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

