

# Overview



Stand sold separate



Unit shown with option F05

## Appliances

### Model 112T

### Model 112, 112+

	112T	112
Standard	V125101.01	V115101.01
Dynamic	V125101.50	V115101.50
Weight	99 kg	168 kg
With Pressure cooking Mode	–	112+
Standard	–	V116101.01
Dynamic	–	V116101.50
Weight	–	186 kg
Mains connection	3 NAC 400 V	3 NAC 400 V
Standard – Connected load	17 kW	17 kW
Standard – Connected load with Ceran	–	19 kW
Dynamic – Connected load	13 kW	13 kW
Dynamic – Connected load with Ceran	–	15 kW
Capacity	2 x 12 dm <sup>2</sup> , 2 x 14 L	2 x 12 dm <sup>2</sup> , 2 x 14 L
Number of meals	from 30	from 30
Width	962 mm	1.200 mm
Depth	800 mm	777 mm
Height	400 mm	1.100 mm
Options		
Vitro Ceran	–	Option F01
Stand with doors and slide-out surfaces (left and right)	–	Option F02
Vitro Ceran and stand with doors (left and right)	–	Option F05
Connection to energy optimising system	Option F03	Option F03
Ethernet interface	Option F06	Option F06
Stainless steel feet	–	Option F27
Hot water connection	–	Option F37

You will find unit-specific accessories on: [Page 7](#)

Appliances presented with options and/or accessories.  
 Combinations of options and other options available upon request.  
 You will find the features on page 4 and 5.  
 Special voltages on request.



# Overview

**NEW**



Stand sold separate

## Appliances

## Model 112L

	112L
Standard	V135101.01
Dynamic	V135101.50
Weight	132 kg
With Pressure cooking Mode	–
Standard	–
Dynamic	–
Weight	–
Mains connection	3 NAC 400 V
Standard – Connected load	28 kW
Dynamic – Connected load	–
Standard – Connected load with Ceran	21 kW
Dynamic – Connected load with Ceran	–
Capacity	2 x 19 dm <sup>3</sup> , 2 x 25 L
Number of meals	50 - 100
Width	1.102 mm
Depth	908 mm
Height	428 mm
Options	
Vitro Ceran	–
Stand with doors and slide-out surfaces (left and right)	–
Vitro Ceran and stand with doors (left and right)	–
Connection to energy optimising system	Option F03
Ethernet interface	Option F06
Stainless steel feet	–
Hot water connection	–

You will find unit-specific accessories on: [Page 9](#)

Appliances presented with options and/or accessories.  
 Combinations of options and other options available upon request.  
 You will find the features on page 4 and 5.  
 Special voltages on request.



# Overview



Appliances	Model 211, 211+	Model 311, 311+
	211	311
Standard	V215101.01	V315101.01
Dynamic	V215101.50	V315101.50
Weight	195 kg	251 kg
With Pressure cooking Mode	211+	311+
Standard	V216101.01	V316101.01
Dynamic	V216101.50	V316101.50
Weight	223 kg	279 kg
Mains connection	3 NAC 400 V	3 NAC 400 V
Standard – Connected load	28 kW	45 kW
Standard – Connected load with Ceran	31 kW	47 kW
Dynamic – Connected load	22 kW	35 kW
Dynamic – Connected load with Ceran	24 kW	37 kW
Capacity	42 dm <sup>3</sup> , 100 L	65 dm <sup>3</sup> , 150 L
Number of meals	100 - 300	100 - 500
Width	1.164 mm	1.542 mm
Depth	914 mm	914 mm
Height	1.100 mm	1.100 mm
Options		
Vitro Ceran	Option F01	Option F01
Connection to energy optimising system	Option F03	Option F03
Ethernet interface	Option F06	Option F06
Stainless steel feet	Option F27	Option F27
Hot water connection	Option F37	Option F37

You will find unit-specific accessories on: [Page 9](#)

Combinations of options and other options available upon request.  
 You will find the features on page 4 and 5.  
 Special voltages on request.

