

# **Induction** appliance with 4 multifunction hobs MS-I-40M, 4×7 kW

Item no. 120825



### Standalone devices of cooking suite quality: Top quality «à la carte» range

A top quality cooker for small restaurants. Maximum flexibility in application. Ideal for «à la carte» cooking as well as for set menu dishes. Four induction hobs controlled independently, designed for everyday use.

## Benefits that are spot on

- Energy saving increased by 50 to 85% as compared to conventional cooking technology
- Minimum heat emission levels allow for an optimum kitchen working environment
- Extremely guick boiling times. Maximum heat output is achieved within just a few seconds.
- Freely adjustable, highly precise energy metering for perfectly cooked food
- Maximum power density per cm<sup>2</sup> at pan base

- Pan type detection (material, size, power consumption properties)
- 2-zone pot detection and temperature monitoring
- Automatic fan monitoring

#### Equipment

Multi-segment digital display Extra-strong ceramic glass Removable grease filter Height-adjustable feet Wall shroud optional

# 5<sup>th</sup>-generation technology

MENU SYSTEM Induction technology



- MENU SYSTEM induction technology is the most up-to-date, highest performing and most advanced induction technology in the world.
- MENU SYSTEM leads the market, developing and producing all the components of this induction technology in-house.
- Its unique position in the field of cooking equipment construction enables the company to concentrate all its efforts on this forwardlooking technology.
- No other company has more experience in the development and application of induction technology in professional kitchens.

#### MS-I-40M Item no. 120825



## Top quality «à la carte» range

4 Multifunction induction hobs 7 kW each

The multifunction hob is ideal for cooking with two to four pans. Thanks to the capacity and high power density of the coil, it's a perfect choice for both production and finishing.

- For 4 saucepans measuring 16 cm or a cooking pot up to 38 cm
- Effective field ø 340 × 360 mm
- 2-zone pot detection and temperature monitoring

## Design


- Hob made from high-quality glass-ceramic material
- Complete housing made from solid stainless steel (Chromium nickel steel 1.4301)
- Removable, easy to clean grease filter
- Height-adjustable feet
- Continuously variable, electronic power control for highly precise energy metering
- One-handed operation using a rotary switch
- Control and power electronics resistant to power supply fluctuations



## **Technical data**

| Dimension       | 800 × 800 × 200 mm |
|-----------------|--------------------|
| Glass dimension | 2 × 360 × 660 mm   |
| Connected load  | 4 x 7 kW           |
|                 | 3×400-440 VAC      |
|                 | 50/60 Hz           |
| Heat emission   | latent 1960 W      |
|                 | sensible 2240 W    |
| Plug            | CEE 32             |
| Cable length    | 3 m                |
| Weight          | 66 kg              |







The experience MENU SYSTEM has gained as the leader of the induction cooking suite market flows directly into the design and development of our standalone appliances. Accordingly, our standalone appliances provide the ideal response to the needs of professionals.



#### **Quality guaranteed**

Our manufacturer's warranty vouches for the quality of our products. Depending on country and region, service and warranties are looked after either by MENU SYSTEM directly or by our authorised partners.



#### Made in Switzerland

With MENU SYSTEM, induction technology, electrical technology and metal-worked components all come from a single source. The high degree of vertical integration guarantees full control based on quality and expertise. For MENU SYSTEM, «Made in Switzerland» isn't just a label— it's a philosophy and a living reality.

MENU SYSTEM AG

cleaned regularly.

Safety instructions

Oberstrasse 222 CH-9014 St.Gallen info@menusystem.ch www.menusystem.ch

The exhaust air must be allowed to escape unobstructed. The grease filters must be

T +41 71 272 51 00 F +41 71 272 51 10