

Optima | 8 | 5 | 0

Product data sheet – Gas griddle plate II – smooth

MKN-No.:
2061107

Cooking appliance according to DIN 18852 for application in the commercial preparation of food in the general catering industry, front cooking, free flow systems and snack bars. For cooking with contact heat, for frying of quick-fried pieces, starch side dishes, egg dishes, desserts such as pancakes and for grilling.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 50 mm at the front and on the sides, bent upwards 25 mm at the rear. Designed as a drip edge at the front on the bottom side. 50 mm cover projection closed to the appliance body. With tightly welded drain channels on the side – rounded (R30) at the rear.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Ergonomically shaped knobs for a easy identification of the position.

Effective area:

Griddle plate with large radii which are easy to clean, seamless and greaseproof, recessed and welded from the top. Two separately adjustable heating zones. Closable fat drain outlet at the front with a removable fat collecting container below.

Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

Type of energy:

Appliance is completely tubed internally in accordance with gas requirements for the gas connection provided by customer.

Special feature:

Heating:

Heating by atmospheric linear burners, thermoelectrically protected. Piezo ignition for the ignition burners to start up the main burner.



Master of Performance

Subject to change without notice!
24.07.2017

Product data sheet – Gas griddle plate II – smooth

MKN-No.:
2061107

Cooking appliance for frying of quick-fried pieces, starch side dishes, egg dishes, desserts such as pancakes and for grilling.

Current drawings you will find here:
www.mkn.eu
▶ service & support
▶ spare parts database & download

Further features

- connection, sealing by special clip bars flush mounted to the cover (optional)
- griddle plate, finely ground, of high temperature resistant steel (1.5415) – 14 mm thick
- thermostatic temperature control with electronic flame monitoring – gas shut off valve installed in appliance for maintenance purposes

Technical data

Dimensions (LxWxH*) (mm):	1000 x 850 x 700
Effective area:	1
Dim.: effect. area (LxWxH) (mm):	900 x 560 x
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage ¹ (V):	
Recommended fuses (A):	
Frequency range (Hz):	50/60
Rated heat load (kW):	14
Standard gas pressure – natural gas ² (mbar):	20
Standard gas pressure – liquid gas ² (mbar):	50 (DE), 30 (EU)
Gas connection:	DN 15 (1/2")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	140
Gross weight ³ (kg):	153
Heat emission latent (W):	5600
Heat emission sensitive (W):	4900
Type of protection:	

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- gas connection provided by customer

Option / accessories

MKN-No.:	Description:
10012737	griddle plate scraper for smooth and ribbed frying surfaces
945230	splash guard for gas griddle plate 2

¹ special voltages on request

² further types of gas on request

³ seaworthy packing on request

