

Product data sheet —Gas lava stone grill Argentina 2

MKN-No.: 2061602

Cooking appliance according to DIN 18852 for application in the commercial preparation of food in the general catering industry, front cooking, free flow systems and snack bars. For cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.

Visible surfaces with polished and satin finish, 320 grit.

Body: Contro

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Effective area:

CNS/stainless steel grid with V-formed grid bars to drain off the dripping liquids into the collecting pan at the front. Grid in 2 parts and adjustable in height. Two adjustable heating zones. Heat distribution by means of the hot glowing stones below.

Type of energy:

Appliance is completely tubed internally in accordance with gas requirements. Gas connection by means of a gas appliance tube attached to a gas socket (DN 15) with shut-off valve.

Bendings:

Cover bent downwards 50 mm at the front and on the sides, bent upwards 25 mm at the rear. Desiged as a drip edge at the front on the bottom side. 50 mm cover projection closed to the appliance body. With tightly welded drain channels on the side – rounded (R30) at the rear.

Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Ergonomiacally shaped knobs for a easy identification of the position.

Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

Special feature:

Heating:

Heating by atmospheric linear burners, thermoelectrically protected. Piezo ignition for the ignition burners to start up the main burner.





Product data sheet —Gas lava stone grill Argentina 2

MKN-No.: 2061602

Cooking appliance for cooking with contact heat, for frying of quick-fried pieces and for grilling meat and vegetables.

Further features

- connection, sealing by special clip bars flush mounted to the cover (optional)
- manual temperature regulation by a tapswitch for each heating zone – inspection hole für ignition burner for each heating zone

Current drawings you will find here: www.mkn.eu

- ► service & support
- ▶ spare parts database & download

Technical data

Dimensions (LxWxH*) (mm):	850 x 850 x 700
Effective area:	2
Dim.: effect. area (LxWxH) (mm):	320 x 510 x
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	
Voltage¹ (V):	
Recommended fuses (A):	
Frequency range (Hz):	50/60
Rated heat load (kW):	16,0
Standard gas pressure – natural gas² (mbar):	20
Standard gas pressure – liquid gas² (mbar):	50 (DE), 30 (EU)
Gas connection:	DN 15 (1/2")
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	112
Gross weight³ (kg):	125
Heat emission latent (W):	3200
Heat emission sensitive (W):	11520
Type of protection:	

^{*} Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

• CE mark

Installation requirements

gas connection provided by customer

Option / accessories

MKN-No.:	Description:
201517	spare lava stones, 1 set

¹ special voltages on request



³ seaworthy packing on request

² further types of gas on request