



Length L, mm	Model	Cut out (mm)	Input	Power
400	UWP1-40/60/14	320 x 520	3,3 A	750 W
500	UWP1-50/60/14	420 x 520	3,3 A	750 W
600	UWP1-60/60/14	520 x 520	3,3 A	750 W
700	UWP1-70/60/14	620 x 520	6,5 A	1500 W
800	UWP1-80/60/14	720 x 520	6,5 A	1500 W
900	UWP1-90/60/14	820 x 520	6,5 A	1500 W
1000	UWP1-100/60/14	920 x 520	9,8 A	2250 W
1100	UWP1-110/60/14	1020 x 520	9,8 A	2250 W
1200	UWP1-120/60/14	1120 x 520	9,8 A	2250 W
1300	UWP1-130/60/14	1220 x 520	13 A	3000 W
1400	UWP1-140/60/14	1320 x 520	13 A	3000 W
1500	UWP1-150/60/14	1420 x 520	13 A	3000 W


<b>Model:</b>	UWP1
<b>Working temperature:</b>	+30 ... +85
<b>Voltage/frequencies:</b>	230-240 V / 50 Hz
<b>Operating type:</b>	Static



Easy service and efficient thermal insulation construction



DROP-IN (easily fits on table top)



Remote control  
Easy-to-clean digital controller with adjustable temperature (+30 ... +85 °C)