


HEATED CUPBOARD WITH SLIDING DOORS



L 800 - 2000 mm

B 600 - 700 mm

H 900 mm



With doors on front and back sides

L	B 600 mm	B 650 mm	B 700 mm			
800 mm	WP0-NLN-80/60/90	WP0-NLN-80/65/90	WP0-NLN-80/70/90	+30 ... +85 °C	9,7 A	2200 W
900 mm	WP0-NLN-90/60/90	WP0-NLN-90/65/90	WP0-NLN-90/70/90	+30 ... +85 °C	9,7 A	2200 W
1000 mm	WP0-NLN-100/60/90	WP0-NLN-100/65/90	WP0-NLN-100/70/90	+30 ... +85 °C	9,7 A	2200 W
1100 mm	WP0-NLN-110/60/90	WP0-NLN-110/65/90	WP0-NLN-110/70/90	+30 ... +85 °C	9,7 A	2200 W
1200 mm	WP0-NLN-120/60/90	WP0-NLN-120/65/90	WP0-NLN-120/70/90	+30 ... +85 °C	9,7 A	2200 W
1300 mm	WP0-NLN-130/60/90	WP0-NLN-130/65/90	WP0-NLN-130/70/90	+30 ... +85 °C	9,7 A	2200 W
1400 mm	WP0-NLN-140/60/90	WP0-NLN-140/65/90	WP0-NLN-140/70/90	+30 ... +85 °C	9,7 A	2200 W
1500 mm	WP0-NLN-150/60/90	WP0-NLN-150/65/90	WP0-NLN-150/70/90	+30 ... +85 °C	9,7 A	2200 W
1600 mm	WP0-NLN-160/60/90	WP0-NLN-160/65/90	WP0-NLN-160/70/90	+30 ... +85 °C	9,7 A	2200 W
1700 mm	WP0-NLN-170/60/90	WP0-NLN-170/65/90	WP0-NLN-170/70/90	+30 ... +85 °C	9,7 A	2200 W
1800 mm	WP0-NLN-180/60/90	WP0-NLN-180/65/90	WP0-NLN-180/70/90	+30 ... +85 °C	9,7 A	2200 W
1900 mm	WP0-NLN-190/60/90	WP0-NLN-190/65/90	WP0-NLN-190/70/90	+30 ... +85 °C	9,7 A	2200 W
2000 mm	WP0-NLN-200/60/90	WP0-NLN-200/65/90	WP0-NLN-200/70/90	+30 ... +85 °C	9,7 A	2200 W