

Serving trolleys - high stability, without welding seams (lightweight version)

Serving trolleys made of stainless steel, tubular pushing handle, deep-drawn shelves with raised edge, sound-deadened, screwed design, max. surface load per shelf 80 kg. Rustproof castors in accordance with DIN 18867, part 1 (exception: galvanised castors). Wheel diameter 125 mm. All serving trolleys have corner bumpers on each shelf, deflector castors and 2 swivel castors, 2 with brakes. Clearance between shelves 585 mm / 275 mm.



assembled/dismantled = flat pack

Type	Shelves	Total height mm	Total carrying capacity in kg	Empty weight kg	Delivery condition	Order no.	
Shelves 800 x 500 mm, serving trolley external dimensions L x W 870 x 570 mm							
SW-850 RL-2M	2	950	120	15	assembled	88 02 50 02	
SW-850 RL-2	2	950	120	15	flat pack	88 02 50 01	
SW-850 RL-2V	2	950	120	15	galvanised castors, flat pack	88 02 50 03	
SW-850 RL-3M	3	950	150	17	assembled	88 02 50 06	
SW-850 RL-3	3	950	150	17	flat pack	88 02 50 05	
SW-850 RL-3V	3	950	150	17	galvanised castors, flat pack	88 02 50 07	
SW-850 RL-4M	4	1260	160	22	assembled	88 02 50 10	
SW-850 RL-4	4	1260	160	22	flat pack	88 02 50 09	
Shelves 1000 x 500 mm, serving trolley external dimensions L x W 1070 x 570 mm							
SW-1050 RL-2M	2	950	120	14	assembled	88 02 50 12	
SW-1050 RL-2	2	950	120	14	flat pack	88 02 50 11	
SW-1050 RL-3M	3	950	150	19	assembled	88 02 50 14	
SW-1050 RL-3	3	950	150	19	flat pack	88 02 50 13	
SW-1050 RL-4M	4	1260	160	25	assembled	88 02 50 16	
SW-1050 RL-4	4	1260	160	25	flat pack	88 02 50 15	
Shelves 1000 x 600 mm, serving trolley external dimensions L x W 1070 x 670 mm							
SW-1060 RL-2M	2	950	120	16	assembled	88 02 50 18	
SW-1060 RL-2	2	950	120	16	flat pack	88 02 50 17	
SW-1060 RL-3M	3	950	150	22	assembled	88 02 50 20	
SW-1060 RL-3	3	950	150	22	flat pack	88 02 50 19	
SW-1060 RL-4M	4	1260	160	28	assembled	88 02 50 22	
SW-1060 RL-4	4	1260	160	28	flat pack	88 02 50 21	

servostar[®] (lightweight version)

Serving trolley made of stainless steel, tubular pushing handle, deep-drawn shelves with raised edge, sound-deadened, screwed design, max. surface load per shelf 80 kg. Rustproof castors in accordance with DIN 18867, part 1 (exception: galvanised castors). Wheel diameter 125 mm. All serving trolleys have corner bumpers on each shelf, deflector castors and 2 swivel castors, 2 swivel castors with brakes.



Type	Shelves	Total height mm	Total carrying capacity in kg	Empty weight kg	Delivery condition	Order no.	
servostar 1/1 light, shelves 630 x 400 mm, serving trolley external dimensions L x W 700 x 470 mm.							
SW-640 RL-2M	2	950	120	12	assembled	88 02 50 35	
SW-640 RL-2	2	950	120	12	flat pack*	88 02 50 36	
SW-640 RL-3M	3	950	150	14.4	assembled	88 02 50 37	
SW-640 RL-3	3	950	150	14.4	flat pack*	88 02 50 38	

Accessories

Glass shelf inserts, dimensions (L x W) 532 x 328, 8 mm thick								
Colour	white	dark blue	pink	black	light blue	dark green	dark grey	dark red
Order no.	72 10 05 81	72 10 05 85	72 10 05 78	72 10 05 80	72 10 05 86	72 10 05 79	72 10 05 82	72 10 05 83
Resopal shelf inserts, dimensions (L x W x H) 532 x 328 x 6 mm								
Colour	walnut	beech						
Order no.	72 10 05 88	72 10 05 89						
Plastic chopping board, dimensions (L x W x H) 557 x 352 x 20 mm			Solid chopping board, (laminated) beech, dimensions (L x W x H) 557 x 352 x 50 mm					
Colour	white			beech				
Order no.	72 10 05 70			72 10 05 71				